



# MODEL 2148 | Specification Sheet

Residential Series • Brass & Copper • Step Light

TYPE:  MODEL:

PROJECT:

## PRODUCT FEATURES



Wattage	4.5 W or 5.5 W
Voltage	9 – 15 VAC
Lumens	295 or 389 Lumens
Lamp Type	MR-16 LED
Housing	Injection-Molded Polymer
Dimensions	5" DIA x 6¼" D

## ORDERING INFORMATION

EXAMPLE: *SL-2148-BSN-4.5-W-36-CFR*

MOUNTING	MODEL	FINISH	LED	ACCESSORIES
SL	2148			

MOUNTING	MODEL	FINISH	LED	ACCESSORIES
SL Step Light	2148	BSN Natural Brass BSO Olde Brass SS Stainless Steel  Also available in 18 standard powder coat finishes. See specifications on pg. 2 for description and order codes.	4.5-W-15 4.5 Watts   Warm   15° Narrow Spot	CFR Crowned Frosted Lens
			4.5-W-25 4.5 Watts   Warm   25° Spot	CBL Crowned Cool Blue Lens
			4.5-W-36 4.5 Watts   Warm   36° Flood	SL Flat Spread Lens
			4.5-W-60 4.5 Watts   Warm   60° Wide Flood	DBL Flat Dark Blue Lens
			5.5-W-15 5.5 Watts   Warm   15° Narrow Spot	GL Flat Dark Green Lens
			5.5-W-25 5.5 Watts   Warm   25° Spot	RL Flat Red Lens
			5.5-W-36 5.5 Watts   Warm   36° Flood	YL Flat Amber Lens
			5.5-W-60 5.5 Watts   Warm   60° Wide Flood	HL Honeycomb louver
			NL No Lamp	



PROFESSIONAL  
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)  
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)  
Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



## SPECIFICATIONS

### HOUSING CONSTRUCTION:

Injection-molded glass-reinforced polymer.

### LENS COVER CONSTRUCTION:

Machined Brass or 304 Stainless Steel.

### FINISH:

Natural Brass, Olde Brass or Natural Stainless Steel lens cover.  
Housing available in black only.

Lens Cover also available in powder coat finish with the following standard colors:  
Black (**B**), Architectural Bronze (**Z**), Dark Bronze (**DZ**), Granite (**GT**), White (**W**),  
Architectural Brick (**BR**), Light Bronze (**LZ**), Special Bronze (**SB**), Glossy Gray (**GG**),  
Rust (**R**), Hunter Green (**HG**), Weathered Bronze (**WB**), Weathered Iron (**WI**),  
Graphite Metallic (**GM**), Verde (**G**), Pewter (**P**), Mocha (**M**) and Olde Finish (**OF**).

### LENS:

Frosted, tempered glass lens.  
Optical effect lenses are available.

### MOUNTING:

Recessed mounting box has two ½" NPT inlets.  
Optional concrete mounting kit available.

### FASTENERS:

All fasteners are stainless steel.

### WIRING:

Provided with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

### CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

### LED:

MR-16 LED Lamp.  
295 or 389 Lumens.  
4.5 or 5.5 Watts.

### ELECTRICAL:

Input voltage range 9 - 15 VAC.  
Low voltage transformer required to operate (sold separately).

### LIGHT DISTRIBUTION:

Very Narrow Spot **15** (15°)  
Narrow Spot **25** (25°)  
Medium Flood **36** (36°)  
Wide Flood **60** (60°)

## DIMENSIONS

