



MODEL 2522 | Specification Sheet
Residential Series • Specialty / Downlight

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES



Wattage	4.5 W or 5.5 W (x2)
Voltage	9 – 15 VAC
Lumens	295 or 389 Lumens
Lamp Type	MR-16 LED (x2)
Housing	Aluminum, Brass or Copper
Dimensions	2 ½" DIA x 6 ¼" H x 4 ½" D

ORDERING INFORMATION

EXAMPLE: **WR-2522-B-4.5-W-36-FR**

CATEGORY	MODEL	FINISH	LED	ACCESSORIES
WR	2522			

CATEGORY	MODEL	FINISH	LED	ACCESSORIES
WR Wall-Mount MB Adjustable Mounting Bracket	2522	B Black R Rust Z Architectural Bronze HG Hunter Green DZ Dark Bronze WB Weathered Bronze GT Granite WI Weathered Iron W White GM Graphite Metallic BR Architectural Brick G Verde LZ Light Bronze P Pewter SB Special Bronze M Mocha GG Glossy Gray OF Olde Finish	4.5-W-15 4.5 Watts Warm 15° Narrow Spot 4.5-W-25 4.5 Watts Warm 25° Spot 4.5-W-36 4.5 Watts Warm 36° Flood 4.5-W-60 4.5 Watts Warm 60° Wide Flood 5.5-W-15 5.5 Watts Warm 15° Narrow Spot 5.5-W-25 5.5 Watts Warm 25° Spot 5.5-W-36 5.5 Watts Warm 36° Flood 5.5-W-60 5.5 Watts Warm 60° Wide Flood NL No Lamp	FR Frosted Lens BL Flat Cool Blue Lens SL Flat Spread Lens DBL Flat Dark Blue Lens GL Flat Dark Green Lens RL Flat Red Lens YL Flat Amber Lens HL Honeycomb louver
		BSN Natural Brass CSN Natural Copper BSS Olde Brass SS Stainless Steel		



**PROFESSIONAL
OUTDOOR LIGHTING**

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

HOUSING CONSTRUCTION:

Available in Aluminum, Brass or Stainless Steel.

FINISH:

Aluminum Housing available with Powder coat finish in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

LENS:

Clear, tempered glass lens.
Optical effect lenses are available.

MOUNTING:

Fixed wall mount assembly or adjustable mounting bracket available.

FASTENERS/INSERTS:

All fasteners are stainless steel.

WIRING:

Prewired with a 12" pigtail of 18-2 SPT1 UV resistant cable and watertight connectors.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

LED:

MR-16 LED Lamp (x2).
295 or 389 Lumens (x2).
4.5 or 5.5 Watts (x2).

LIGHT DISTRIBUTION:

Very Narrow Spot **15** (15°)
Narrow Spot **25** (25°)
Medium Flood **36** (36°)
Wide Flood **60** (60°)

ELECTRICAL:

Input voltage range 9 - 15 VAC.
Low voltage transformer required to operate (sold separately).

DIMENSIONS

