



MODEL 2141 | Specification Sheet

Residential Series • Brass & Copper • Step Light

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES



Wattage	1 – 5 W
Voltage	9 – 15 VAC
Faceplate	Brass, Copper or Stainless Steel
Dimensions	4 ¾" L x 2 7⁄8" H x 3 ½" D

ORDERING INFORMATION

EXAMPLE: **SL-2141-BSN-W-LB5ND**

CATEGORY	MODEL	FINISH	LED
SL	2141		

CATEGORY	MODEL	FINISH	LED
SL Step Light	2141	BSN Natural Brass	W-LB2ND 2.5 Watts Warm Integrated LED
		BSO Olde Brass	N-LB2ND 2.5 Watts Neutral Integrated LED
		CSN Natural Copper	C-LB2ND 2.5 Watts Cool Integrated LED
		SS Stainless Steel	W-LB5ND 5 Watts Warm Integrated LED
		Also available in 18 standard powder coat finishes. See specifications on pg. 2 for description and order codes.	N-LB5ND 5 Watts Neutral Integrated LED
			C-LB5ND 5 Watts Cool Integrated LED
			150-W-G4 1.5 Watts Warm G4 LED Lamp
		NL No Lamp	



PROFESSIONAL
OUTDOOR LIGHTING



SPECIFICATIONS

HOUSING CONSTRUCTION:

Stamped & formed aluminum recessed box with ½" knockouts on the back & side.

COVER PLATE CONSTRUCTION:

Stamped solid brass, copper, or stainless steel.

FINISH:

Brushed Natural Copper, Natural Brass, Olde Brass finish or Stainless Steel.
(Brushed copper will rapidly age to an elegant rich bronze-like color and may develop areas of patina over time.

Lens Cover also available in powder coat finish with the following standard colors:
Black (**B**), Architectural Bronze (**Z**), Dark Bronze (**DZ**), Granite (**GT**), White (**W**),
Architectural Brick (**BR**), Light Bronze (**LZ**), Special Bronze (**SB**), Glossy Gray (**GG**),
Rust (**R**), Hunter Green (**HG**), Weathered Bronze (**WB**), Weathered Iron (**WI**),
Graphite Metallic (**GM**), Verde (**G**), Pewter (**P**), Mocha (**M**) and Olde Finish (**OF**).

LENS:

Translucent, high-impact polycarbonate lens.

MOUNTING:

Recessed mounting box included.

FASTENERS:

All fasteners are stainless steel.

WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

LED:

- Integrated LED Module. 2.5 – 5 Watts.
- G4 LED Lamp. 1.5 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC.
Low voltage transformer required to operate (sold separately).

DIMENSIONS

