



# MODEL 2147 | Specification Sheet

Residential Series • Brass & Copper • Step Light

TYPE:  MODEL:

PROJECT:

## PRODUCT FEATURES



Wattage	4.5 W or 5.5 W
Voltage	9 – 15 VAC
Lumens	295 or 389 Lumens
Lamp Type	MR-16 LED
Housing	Injection-Molded Polymer
Dimensions	5" DIA x 5" D

## ORDERING INFORMATION

EXAMPLE: *SL-2147-BSN-4.5-W-36-CFR*

MOUNTING	MODEL	FINISH	LED	ACCESSORIES
SL	2147			

MOUNTING	MODEL	FINISH	LED	ACCESSORIES
SL Step Light	2147	BSN Natural Brass	4.5-W-15 4.5 Watts   Warm   15° Narrow Spot	CFR Crowned Frosted Lens
		BSO Olde Brass	4.5-W-25 4.5 Watts   Warm   25° Spot	CBL Crowned Cool Blue Lens
		SS Stainless Steel	4.5-W-36 4.5 Watts   Warm   36° Flood	SL Flat Spread Lens
			4.5-W-60 4.5 Watts   Warm   60° Wide Flood	DBL Flat Dark Blue Lens
		Also available in 18 standard powder coat finishes. See specifications on pg. 2 for description and order codes.	5.5-W-15 5.5 Watts   Warm   15° Narrow Spot	GL Flat Dark Green Lens
			5.5-W-25 5.5 Watts   Warm   25° Spot	RL Flat Red Lens
			5.5-W-36 5.5 Watts   Warm   36° Flood	YL Flat Amber Lens
			5.5-W-60 5.5 Watts   Warm   60° Wide Flood	HL Honeycomb louver
			NL No Lamp	



PROFESSIONAL  
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)  
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)  
Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



## SPECIFICATIONS

### HOUSING CONSTRUCTION:

Injection-molded glass-reinforced polymer.

### LENS COVER CONSTRUCTION:

Machined Brass or 304 Stainless Steel.

### FINISH:

Natural Brass, Olde Brass or Natural Stainless Steel lens cover.  
Housing available in black only.

Lens Cover also available in powder coat finish with the following standard colors:  
Black (**B**), Architectural Bronze (**Z**), Dark Bronze (**DZ**), Granite (**GT**), White (**W**),  
Architectural Brick (**BR**), Light Bronze (**LZ**), Special Bronze (**SB**), Glossy Gray (**GG**),  
Rust (**R**), Hunter Green (**HG**), Weathered Bronze (**WB**), Weathered Iron (**WI**),  
Graphite Metallic (**GM**), Verde (**G**), Pewter (**P**), Mocha (**M**) and Olde Finish (**OF**).

### LENS:

Frosted, tempered glass lens.  
Optical effect lenses are available.

### MOUNTING:

Recessed mounting box has two ½" NPT inlets.  
Optional concrete mounting kit available.

### FASTENERS:

All fasteners are stainless steel.

### WIRING:

Provided with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

### CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

### LED:

MR-16 LED Lamp.  
295 or 389 Lumens.  
4.5 or 5.5 Watts.

### ELECTRICAL:

Input voltage range 9 - 15 VAC.  
Low voltage transformer required to operate (sold separately).

### LIGHT DISTRIBUTION:

Very Narrow Spot **15** (15°)  
Narrow Spot **25** (25°)  
Medium Flood **36** (36°)  
Wide Flood **60** (60°)

## DIMENSIONS

