

TYPE:	MODEL:

PRODU	JCT FE <i>F</i>	ATURES
-------	-----------------	--------



Wattage	5 W
Voltage	9 – 15 VAC
ССТ	3000K (WARM) 4000K (NEUTRAL) 5000K (COOL)
Housing	Brass or Stainless Steel
Dimensions	2%" DIA x 3½" D

ORDERING INFORMATION

EXAMPLE: UW-2119-BSN-W-LC5ND

CATEGORY MODEL FINISH LED

UW 2119

CATEGORY	MODEL	FINISH	LED	ORDERING NOTES
UW Underwater	2119	BSN Natural Brass	W-LC5ND 5 Watts Warm Integrated LED	2119 NOT for use in swimming
		SS Stainless Steel	N-LC5ND 5 Watts Neutral Integrated LED	pools or spas.
			C-LC5ND 5 Watts Cool Integrated LED	
		Also available in 18 standard powder coat finishes. See specifications on pg. 2 for description and order codes.		







SPECIFICATIONS

HOUSING CONSTRUCTION:

Machined brass or stainless steel.

FINISH:

Natural Brass or Stainless Steel.

Also available in powder coat finish with the following standard colors: Black (B), Architectural Bronze (Z), Dark Bronze (DZ), Granite (GT), White (W), Architectural Brick (BR), Light Bronze (LZ), Special Bronze (SB), Glossy Gray (GG), Rust (R), Hunter Green (HG), Weathered Bronze (WB), Weathered Iron (WI), Graphite Metallic (GM), Verde (G), Pewter (P), Mocha (M) and Olde Finish (OF).

LENS:

Clear, tempered soda-lime glass lens.

MOUNTING:

Solid brass or stainless steel mounting bracket allows $\pm 20^{\circ}$ of adjustment.

FASTENERS:

All fasteners are stainless steel.

WIRING

Pre-wired with a fifteen-foot pigtail of 18-3 submersible cable. Connectors for a required above-water connection are also included.

LED:

Integrated LED Module. 5 Watts.

COLOR TEMPERATURE:

3000K, 4000K or 5000K CCT White.

ELECTRICAL:

Input voltage range 9 - 15 VAC. Low voltage transformer required to operate (sold separately).

CAUTION:

Follow installation instructions as well as local electrical codes when installing. **NOT** for use in swimming pools or spas.

DIMENSIONS



