

	MODEL:
PROJECT:	

## **PRODUCT FEATURES**



Wattage	2.5 – 5 W
Voltage	9 – 15 VAC
Housing	Injection-Molded Polymer
Dimensions	4¾" DIA x 3" H



# **ORDERING INFORMATION**

EXAMPLE: **UW-4217-B-W-LB5ND-DBL** 

CATEGORY	MODEL	FINISH	LED	ACCESSORIES
UW	4217	В		

CATEGORY	MODEL	FINISH	LED	ACCESSORIES
<b>UW</b> Underwater	4217	<b>B</b> Black	W-LB2ND 2.5 Watts   Warm   Integrated LED	DBL Dark Blue Lens
			N-LB2ND 2.5 Watts   Neutral   Integrated LED	GL Dark Green Lens
			C-LB2ND 2.5 Watts   Cool   Integrated LED	RL Red Lens
			W-LB5ND 5 Watts   Warm   Integrated LED	YL Amber Lens
			N-LB5ND 5 Watts   Neutral   Integrated LED	
			C-LB5ND 5 Watts   Cool   Integrated LED	
			<b>150-W-G4</b> 1.5 Watts   Warm   G4 LED Lamp	
			<b>NL</b> No Lamp	
				ORDERING NOTES
				4217 <b>NOT</b> for use in swimming pools or spas.





### **SPECIFICATIONS**

## HOUSING CONSTRUCTION:

Injection-molded polymer.

### LENS CONSTRUCTION:

Injection-molded polycarbonate.

#### LENS:

Clear prismatic spread lens. Optical effect lenses are available.

### REFLECTOR:

Removable mirror-finish reflector to block up light and provide wider horizontal spread.

### **FASTENERS:**

All fasteners are stainless steel.

### WIRING:

Pre-wired with a fifteen-foot pigtail of 18-3 submersible cable. Connectors for a required above-water connection are also included.

### CAUTION

Follow installation instructions as well as local electrical codes when installing. **NOT** for use in swimming pools or spas.

## LED:

- Integrated LED Module. 2.5 5 Watts.
- G4 LED Lamp. 1.5 Watts.

### **ELECTRICAL:**

Input voltage range 9 - 15 VAC. Low voltage transformer required to operate (sold separately).

# **DIMENSIONS**





