



MODEL **2145** | Specification Sheet
Residential Series • Brass & Copper • Step Light

TYPE:

MODEL:

PROJECT:

PRODUCT FEATURES



| | |
|------------|----------------------------------|
| Wattage | 1 – 5 W |
| Voltage | 9 – 15 VAC |
| Faceplate | Brass, Copper or Stainless Steel |
| Dimensions | 9 1⁄8" L x 2 7⁄8" H x 3 1⁄2" D |

ORDERING INFORMATION

EXAMPLE: SL-2145-BSN-W-LC5ND

| CATEGORY | MODEL | FINISH | LED |
|----------|-------|--------|-----|
| SL | 2145 | | |

| CATEGORY | MODEL | FINISH | LED |
|---------------|-------|--|---|
| SL Step Light | 2145 | BSN Natural Brass | W-LC5ND 5 Watts Warm Integrated LED |
| | | BSO Olde Brass | N-LC5ND 5 Watts Neutral Integrated LED |
| | | CSN Natural Copper | C-LC5ND 5 Watts Cool Integrated LED |
| | | SS Stainless Steel | 2.5-W-G-T3 2.5 Watts Warm T3 LED Lamp |
| | | | 150-W-G4 1.5 Watts Warm G4 LED Lamp (x 2) |
| | | Also available in 18 standard powder coat finishes. See specifications on pg. 2 for description and order codes. | NL No Lamp |



PROFESSIONAL
OUTDOOR LIGHTING



SPECIFICATIONS

HOUSING CONSTRUCTION:

Stamped & formed aluminum recessed box with ½" knockouts on the back & side.

COVER PLATE CONSTRUCTION:

Stamped solid brass, copper, or stainless steel.

FINISH:

Brushed Natural Copper, Natural Brass, Olde Brass finish or Stainless Steel.
(Brushed copper will rapidly age to an elegant rich bronze-like color and may develop areas of patina over time.

Lens Cover also available in powder coat finish with the following standard colors:
Black (B), Architectural Bronze (Z), Dark Bronze (DZ), Granite (GT), White (W),
Architectural Brick (BR), Light Bronze (LZ), Special Bronze (SB), Glossy Gray (GG),
Rust (R), Hunter Green (HG), Weathered Bronze (WB), Weathered Iron (WI),
Graphite Metallic (GM), Verde (G), Pewter (P), Mocha (M) and Olde Finish (OF).

LENS:

Translucent, high-impact polycarbonate lens.

MOUNTING:

Recessed mounting box included.

FASTENERS:

All fasteners are stainless steel.

WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

LED:

- Integrated LED Module. 5 Watts.
- G4 LED Lamp (x 2). 1.5 Watts (x 2).

ELECTRICAL:

Input voltage range 9 - 15 VAC.
Low voltage transformer required to operate (sold separately).

DIMENSIONS

