



MODEL 2125 | Specification Sheet

Residential Series • Brass & Copper • Path & Area

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES



Wattage	1 – 5 W
Voltage	9 – 15 VAC
Housing	Copper or Brass
Dimensions	6" DIA x 13 1/4" H

ORDERING INFORMATION

EXAMPLE: **PR-2125-BSN-W-LB5ND**

MOUNTING	MODEL	FINISH	LED
PR	2125		

MOUNTING	MODEL	FINISH	LED
PR ABS Ground Stake	2125	CSN Natural Copper	W-LB2ND 2.5 Watts Warm Integrated LED
		BSN Natural Brass	N-LB2ND 2.5 Watts Neutral Integrated LED
		BSO Olde Brass	C-LB2ND 2.5 Watts Cool Integrated LED
		Also available in 18 standard powder coat finishes. See specifications on pg. 2 for description and order codes.	W-LB5ND 5 Watts Warm Integrated LED
			N-LB5ND 5 Watts Neutral Integrated LED
			C-LB5ND 5 Watts Cool Integrated LED
			150-W-G4 1.5 Watts Warm G4 LED Lamp
			NL No Lamp



PROFESSIONAL
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)
Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

HOUSING CONSTRUCTION:

Solid Copper or Brass shade.
Twist-To-Lock Solid Brass lamp base.

STEM CONSTRUCTION:

½" Solid Copper or Brass pipe.

FINISH:

Brushed Natural Copper, Natural Brass or Olde Brass finish.
(Brushed copper will rapidly age to an elegant rich bronze-like color and may develop areas of patina over time.

Also available in powder coat finish with the following standard colors:
Black (B), Architectural Bronze (Z), Dark Bronze (DZ), Granite (GT), White (W),
Architectural Brick (BR), Light Bronze (LZ), Special Bronze (SB), Glossy Gray (GG),
Rust (R), Hunter Green (HG), Weathered Bronze (WB), Weathered Iron (WI),
Graphite Metallic (GM), Verde (G), Pewter (P), Mocha (M) and Olde Finish (OF).

LENS:

Textured, high-impact polycarbonate lens.

MOUNTING:

Bottom of stem threaded with ½" NPT.

FASTENERS:

All fasteners are stainless steel.

WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

LED:

- Integrated LED Module. 2.5 – 5 Watts.
- G4 LED Lamp. 1.5 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC.
Low voltage transformer required to operate (sold separately).

DIMENSIONS

