



# MODEL 2130 | Specification Sheet

Residential Series • Brass & Copper • Path & Area

TYPE:  MODEL:

PROJECT:

## PRODUCT FEATURES



Wattage	1 – 5 W
Voltage	9 – 15 VAC
Housing	Copper or Brass
Dimensions	7" DIA x 13" H

## ORDERING INFORMATION

EXAMPLE: **PR-2130-BSN-W-LB5ND**

MOUNTING	MODEL	FINISH	LED
PR	2130		

MOUNTING	MODEL	FINISH	LED
PR ABS Ground Stake	2130	CSN Natural Copper	W-LB2ND 2.5 Watts   Warm   Integrated LED
		BSN Natural Brass	N-LB2ND 2.5 Watts   Neutral   Integrated LED
		BSO Olde Brass	C-LB2ND 2.5 Watts   Cool   Integrated LED
		Also available in 18 standard powder coat finishes. See specifications on pg. 2 for description and order codes.	W-LB5ND 5 Watts   Warm   Integrated LED
			N-LB5ND 5 Watts   Neutral   Integrated LED
			C-LB5ND 5 Watts   Cool   Integrated LED
			150-W-G4 1.5 Watts   Warm   G4 LED Lamp
			NL No Lamp



PROFESSIONAL  
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)  
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)  
Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



## SPECIFICATIONS

### HOUSING CONSTRUCTION:

Solid Copper or Brass shade.  
Twist-To-Lock Solid Brass lamp base.

### STEM CONSTRUCTION:

½" Solid Copper or Brass pipe.

### FINISH:

Brushed Natural Copper, Natural Brass or Olde Brass finish.  
(Brushed copper will rapidly age to an elegant rich bronze-like color and may develop areas of patina over time.

Also available in powder coat finish with the following standard colors:  
Black (**B**), Architectural Bronze (**Z**), Dark Bronze (**DZ**), Granite (**GT**), White (**W**),  
Architectural Brick (**BR**), Light Bronze (**LZ**), Special Bronze (**SB**), Glossy Gray (**GG**),  
Rust (**R**), Hunter Green (**HG**), Weathered Bronze (**WB**), Weathered Iron (**WI**),  
Graphite Metallic (**GM**), Verde (**G**), Pewter (**P**), Mocha (**M**) and Olde Finish (**OF**).

### LENS:

Textured, high-impact polycarbonate lens.

### MOUNTING:

Bottom of stem threaded with ½" NPT.

### FASTENERS:

All fasteners are stainless steel.

### WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

### CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

### LED:

- Integrated LED Module. 2.5 – 5 Watts.
- G4 LED Lamp. 1.5 Watts.

### ELECTRICAL:

Input voltage range 9 - 15 VAC.  
Low voltage transformer required to operate (sold separately).

## DIMENSIONS

