



MODEL 2104 | Specification Sheet

Residential Series • Brass & Copper • Up / Accent

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES



Wattage	1 – 5 W
Voltage	9 – 15 VAC
Housing	Copper or Brass
Dimensions	5 ½" DIA x 6 7⁄8" H x 2 ¾" D

ORDERING INFORMATION

EXAMPLE: GR-2104-CSN-W-LB5ND

MOUNTING	MODEL	FINISH	LED
	2104		

MOUNTING	MODEL	FINISH	LED
GR ABS Ground Stake WB Brass Wall-Mount Canopy	2104	CSN Natural Copper BSN Natural Brass BSO Olde Brass Also available in 18 standard powder coat finishes. See specifications on pg. 2 for description and order codes.	W-LB2ND 2.5 Watts Warm Integrated LED N-LB2ND 2.5 Watts Neutral Integrated LED C-LB2ND 2.5 Watts Cool Integrated LED W-LB5ND 5 Watts Warm Integrated LED N-LB5ND 5 Watts Neutral Integrated LED C-LB5ND 5 Watts Cool Integrated LED 150-W-G4 1.5 Watts Warm G4 LED Lamp NL No Lamp



PROFESSIONAL
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)
Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

CONSTRUCTION:

Spun solid copper or brass.

FINISH:

Natural Copper, Natural Brass or Olde Brass finish.
(Brushed copper will rapidly age to an elegant rich bronze-like color and may develop areas of patina over time.

Also available in powder coat finish with the following standard colors:
Black (**B**), Architectural Bronze (**Z**), Dark Bronze (**DZ**), Granite (**GT**), White (**W**),
Architectural Brick (**BR**), Light Bronze (**LZ**), Special Bronze (**SB**), Glossy Gray (**GG**),
Rust (**R**), Hunter Green (**HG**), Weathered Bronze (**WB**), Weathered Iron (**WI**),
Graphite Metallic (**GM**), Verde (**G**), Pewter (**P**), Mocha (**M**) and Olde Finish (**OF**).

LENS:

Frosted, high-impact polycarbonate lens.

MOUNTING:

Injection-molded composite knuckle with 1/2" NPS thread.

FASTENERS:

All fasteners are stainless steel.

WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

LED:

- Integrated LED Module. 2.5 – 5 Watts.
- G4 LED Lamp. 1.5 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC.
Low voltage transformer required to operate (sold separately).

DIMENSIONS

