

TYPE:	MODEL:
PROJECT:	

PRODUCT FEATURES

Wattage	1.5 W
Voltage	9 – 15 VAC
Housing	Aluminum
Dimensions	4" DIA x 15 %" H

2265



150-W-G4



EXAMPLE: **PR-2265-B-150-W-G4**

ORDERING INFORMATION

PR

MOUNTING MODEL FINISH LED

MOUNTING **MODEL FINISH LED ORDERING NOTES** PR ABS Ground Stake 2265 **150-W-G4** 1.5 Watts | Warm | G4 LED Lamp **B** Black Fixtures shipped with specified mounting hardware. Z Architectural Bronze DZ Dark Bronze Custom length stems available -Consult local distributor. GT Granite W White BR Architectural Brick LZ Light Bronze SB Special Bronze **GG** Glossy Gray R Rust HG Hunter Green WB Weathered Bronze WI Weathered Iron **GM** Graphite Metallic Verde G P Pewter M Mocha **OF** Olde Finish



SPECIFICATIONS

HOUSING CONSTRUCTION:

Die-cast A360 aluminum.

STEM CONSTRUCTION:

½" schedule-40 aluminum pipe.

FINISH

Powder coat finish available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish

I FNS

Clear, high-impact polycarbonate lens.

MOUNTING:

Bottom of stem threaded with ½" NPT.

LED:

G4 LED Lamp. 1.5 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC. Low voltage transformer required to operate (sold separately).

FASTENERS:

All fasteners are stainless steel.

WIRING

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

CERTIFICATION

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

DIMENSIONS





