



MODEL 2146 | Specification Sheet

Residential Series • Brass & Copper • Step Light

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES



Wattage	1 – 5 W
Voltage	9 – 15 VAC
Faceplate	Brass, Copper or Stainless Steel
Dimensions	9 1/8" L x 2 7/8" H x 3 1/2" D

ORDERING INFORMATION

EXAMPLE: SL-2146-BSN-W-LC5ND

CATEGORY	MODEL	FINISH	LED
SL	2146		
SL Step Light	2146	BSN Natural Brass	W-LC5ND 5 Watts Warm Integrated LED
		BSO Olde Brass	N-LC5ND 5 Watts Neutral Integrated LED
		CSN Natural Copper	C-LC5ND 5 Watts Cool Integrated LED
		SS Stainless Steel	2.5-W-G-T3 2.5 Watts Warm T3 LED Lamp
			150-W-G4 1.5 Watts Warm G4 LED Lamp (x 2)
		Also available in 18 standard powder coat finishes. See specifications on pg. 2 for description and order codes.	NL No Lamp



PROFESSIONAL
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)
Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

HOUSING CONSTRUCTION:

Stamped & formed aluminum recessed box with ½" knockouts on the back & side.

COVER PLATE CONSTRUCTION:

Stamped solid brass, copper, or stainless steel.

FINISH:

Brushed Natural Copper, Natural Brass, Olde Brass finish or Stainless Steel.
(Brushed copper will rapidly age to an elegant rich bronze-like color and may develop areas of patina over time.

Lens Cover also available in powder coat finish with the following standard colors:
Black (B), Architectural Bronze (Z), Dark Bronze (DZ), Granite (GT), White (W),
Architectural Brick (BR), Light Bronze (LZ), Special Bronze (SB), Glossy Gray (GG),
Rust (R), Hunter Green (HG), Weathered Bronze (WB), Weathered Iron (WI),
Graphite Metallic (GM), Verde (G), Pewter (P), Mocha (M) and Olde Finish (OF).

LENS:

Translucent, high-impact polycarbonate lens.

MOUNTING:

Recessed mounting box included.

FASTENERS:

All fasteners are stainless steel.

WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

LED:

- Integrated LED Module. 5 Watts.
- G4 LED Lamp (x 2). 1.5 Watts (x 2).

ELECTRICAL:

Input voltage range 9 - 15 VAC.
Low voltage transformer required to operate (sold separately).

DIMENSIONS

