



MODEL 2350 | Specification Sheet

Residential Series • Up / Accent / Downlight

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES



Wattage	4.5 W or 5.5 W
Voltage	9 – 15 VAC
Lumens	295 or 389 Lumens
Lamp Type	MR-16 LED
Housing	Brass
Dimensions	2 1/2" DIA x 6 3/4" D

ORDERING INFORMATION

EXAMPLE: GR-2350-BSN-4.5-W-36-FR

CATEGORY	MODEL	FINISH	LED
	2350		

CATEGORY	MODEL	FINISH	LED	ACCESSORIES
GR ABS Ground Stake WB Brass Wall-Mount Canopy	2350	BSN Natural Brass BSO Olde Brass Also available in 18 standard powder coat finishes. See specifications on pg. 2 for description and order codes.	4.5-W-15 4.5 Watts Warm 15° Narrow Spot 4.5-W-25 4.5 Watts Warm 25° Spot 4.5-W-36 4.5 Watts Warm 36° Flood 4.5-W-60 4.5 Watts Warm 60° Wide Flood 5.5-W-15 5.5 Watts Warm 15° Narrow Spot 5.5-W-25 5.5 Watts Warm 25° Spot 5.5-W-36 5.5 Watts Warm 36° Flood 5.5-W-60 5.5 Watts Warm 60° Wide Flood NL No Lamp	BL Flat Cool Blue Lens SL Flat Spread Lens DBL Flat Dark Blue Lens GL Flat Dark Green Lens RL Flat Red Lens YL Flat Amber Lens HL Honeycomb louver



PROFESSIONAL
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)
Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

HOUSING CONSTRUCTION:

Solid Brass.

FINISH:

Natural Brass or Olde Brass finish.

Also available in powder coat finish with the following standard colors:

Black (**B**), Architectural Bronze (**Z**), Dark Bronze (**DZ**), Granite (**GT**), White (**W**), Architectural Brick (**BR**), Light Bronze (**LZ**), Special Bronze (**SB**), Glossy Gray (**GG**), Rust (**R**), Hunter Green (**HG**), Weathered Bronze (**WB**), Weathered Iron (**WI**), Graphite Metallic (**GM**), Verde (**G**), Pewter (**P**), Mocha (**M**) and Olde Finish (**OF**).

LENS:

Clear, tempered glass lens.

Optical effect lenses are available.

LED:

MR-16 LED Lamp.

295 or 389 Lumens.

4.5 or 5.5 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC.

Low voltage transformer required to operate (sold separately).

MOUNTING:

Solid Brass knuckle with 1/2" NPS thread.

FASTENERS/INSERTS:

Fasteners are stainless steel and brass.

WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

DIMENSIONS

