



MODEL 2115 | Specification Sheet

Residential Series • Brass & Copper • Underwater

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES



Wattage	2.5 – 5 W
Voltage	9 – 15 VAC
CCT	3000K (WARM) 4000K (NEUTRAL) 5000K (COOL)
Housing	Brass or Stainless Steel
Dimensions	2 7/8" DIA x 3 1/2" D

ORDERING INFORMATION

EXAMPLE: UW-2115-BSN-W-LB5ND

CATEGORY	MODEL	FINISH	LED
UW	2115		

CATEGORY	MODEL	FINISH	LED	ORDERING NOTES
UW Underwater	2115	BSN Natural Brass	W-LB2ND 2.5 Watts Warm Integrated LED	2115 NOT for use in swimming pools or spas.
		SS Stainless Steel	N-LB2ND 2.5 Watts Neutral Integrated LED	
			C-LB2ND 2.5 Watts Cool Integrated LED	
		Also available in 18 standard powder coat finishes. See specifications on pg. 2 for description and order codes.	W-LB5ND 5 Watts Warm Integrated LED	
			N-LB5ND 5 Watts Neutral Integrated LED	
			C-LB5ND 5 Watts Cool Integrated LED	



PROFESSIONAL
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)
Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

HOUSING CONSTRUCTION:

Machined brass or stainless steel.

FINISH:

Natural Brass or Stainless Steel.

Also available in powder coat finish with the following standard colors:

Black (**B**), Architectural Bronze (**Z**), Dark Bronze (**DZ**), Granite (**GT**), White (**W**), Architectural Brick (**BR**), Light Bronze (**LZ**), Special Bronze (**SB**), Glossy Gray (**GG**), Rust (**R**), Hunter Green (**HG**), Weathered Bronze (**WB**), Weathered Iron (**WI**), Graphite Metallic (**GM**), Verde (**G**), Pewter (**P**), Mocha (**M**) and Olde Finish (**OF**).

LENS:

Clear, tempered soda-lime glass lens.

MOUNTING:

Solid brass or stainless steel mounting bracket allows $\pm 20^\circ$ of adjustment.

FASTENERS:

All fasteners are stainless steel.

WIRING:

Pre-wired with a fifteen-foot pigtail of 18-3 submersible cable.
Connectors for a required above-water connection are also included.

LED:

Integrated LED Module.
2.5 – 5 Watts.

COLOR TEMPERATURE:

3000K, 4000K or 5000K CCT White.

ELECTRICAL:

Input voltage range 9 - 15 VAC.
Low voltage transformer required to operate (sold separately).

CAUTION:

Follow installation instructions as well as local electrical codes when installing.

NOT for use in swimming pools or spas.

DIMENSIONS

