



# MODEL 2162 | Specification Sheet

Residential Series • Brass & Copper • Path & Area

TYPE:  MODEL:

PROJECT:

## PRODUCT FEATURES

Wattage	1 – 5 W
Voltage	9 – 15 VAC
Housing	Stainless Steel and Brass
Dimensions	4 ½" DIA x 16 ½" H



## ORDERING INFORMATION

EXAMPLE: **PR-2162-SS-W-LB5ND**

MOUNTING	MODEL	FINISH	LED
PR	2162		

MOUNTING	MODEL	FINISH	LED
PR ABS Ground Stake	2162	SS Natural Stainless Steel	W-LB2ND 2.5 Watts   Warm   Integrated LED
			N-LB2ND 2.5 Watts   Neutral   Integrated LED
			C-LB2ND 2.5 Watts   Cool   Integrated LED
			W-LB5ND 5 Watts   Warm   Integrated LED
			N-LB5ND 5 Watts   Neutral   Integrated LED
			C-LB5ND 5 Watts   Cool   Integrated LED
		Also available in 18 standard powder coat finishes. See specifications on pg. 2 for description and order codes.	150-W-G4 1.5 Watts   Warm   G4 LED Lamp
			NL No Lamp



PROFESSIONAL  
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)  
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)  
Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



## SPECIFICATIONS

### HOUSING CONSTRUCTION:

Stainless Steel shade.  
Twist-To-Lock Solid Brass lamp base.

### STEM CONSTRUCTION:

½" Stainless Steel pipe.

### FINISH:

Natural Stainless Steel.

Also available in powder coat finish with the following standard colors:  
Black (B), Architectural Bronze (Z), Dark Bronze (DZ), Granite (GT), White (W),  
Architectural Brick (BR), Light Bronze (LZ), Special Bronze (SB), Glossy Gray (GG),  
Rust (R), Hunter Green (HG), Weathered Bronze (WB), Weathered Iron (WI),  
Graphite Metallic (GM), Verde (G), Pewter (P), Mocha (M) and Olde Finish (OF).

### LENS:

Textured, high-impact polycarbonate lens.

### MOUNTING:

Bottom of stem threaded with ½" NPT.

### FASTENERS:

All fasteners are stainless steel.

### WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

### CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

### LED:

- Integrated LED Module. 2.5 – 5 Watts.
- G4 LED Lamp. 1.5 Watts.

### ELECTRICAL:

Input voltage range 9 - 15 VAC.  
Low voltage transformer required to operate (sold separately).

## DIMENSIONS

