



MODEL 2104 | Specification Sheet
Residential Series • Brass & Copper • Up / Accent

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES



Wattage	1 – 5 W
Voltage	9 – 15 VAC
Housing	Copper or Brass
Dimensions	5 1/2" DIA x 6 7/8" H x 2 3/8" D

ORDERING INFORMATION

EXAMPLE: **GR-2104-CSN-W-LB5ND**

MOUNTING	MODEL	FINISH	LED
	2104		

MOUNTING	MODEL	FINISH	LED
GR ABS Ground Stake WR Wall-Mount Canopy	2104	CSN Natural Copper BSN Natural Brass BSO Olde Brass	W-LB2ND 2.5 Watts Warm Integrated LED
			N-LB2ND 2.5 Watts Neutral Integrated LED
			C-LB2ND 2.5 Watts Cool Integrated LED
			W-LB5ND 5 Watts Warm Integrated LED
			N-LB5ND 5 Watts Neutral Integrated LED
			C-LB5ND 5 Watts Cool Integrated LED
			150-W-G4 1.5 Watts Warm G4 LED Lamp
			NL No Lamp



**PROFESSIONAL
OUTDOOR LIGHTING**

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

CONSTRUCTION:

Spun solid copper or brass.

FINISH:

Natural Copper, Natural Brass or Olde Brass.

LENS:

Frosted, high-impact polycarbonate lens.

MOUNTING:

Injection-molded composite knuckle with 1/2" NPS thread.

FASTENERS:

All fasteners are stainless steel.

WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

LED:

- Integrated LED Module. 2.5 – 5 Watts.
- G4 LED Lamp. 1.5 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC.

Low voltage transformer required to operate (sold separately).

DIMENSIONS

