



MODEL 4217 | Specification Sheet
Residential Series • Specialty / Underwater

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES



Wattage	2.5 – 5 W
Voltage	9 – 15 VAC
Housing	Injection-Molded Polymer
Dimensions	4 ¾" DIA x 3" H



ORDERING INFORMATION

EXAMPLE: UW-4217-B-W-LB5ND-DBL

CATEGORY	MODEL	FINISH	LED	ACCESSORIES
UW	4217	B		

CATEGORY	MODEL	FINISH	LED	ACCESSORIES
UW Underwater	4217	B Black	W-LB2ND 2.5 Watts Warm Integrated LED	DBL Dark Blue Lens GL Dark Green Lens RL Red Lens YL Amber Lens
			N-LB2ND 2.5 Watts Neutral Integrated LED	
			C-LB2ND 2.5 Watts Cool Integrated LED	
			W-LB5ND 5 Watts Warm Integrated LED	
			N-LB5ND 5 Watts Neutral Integrated LED	
			C-LB5ND 5 Watts Cool Integrated LED	
			ORDERING NOTES	
4217 NOT for use in swimming pools or spas.				



PROFESSIONAL
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

HOUSING CONSTRUCTION:

Injection-molded polymer.

LENS CONSTRUCTION:

Injection-molded polycarbonate.

LENS:

Clear prismatic spread lens.
Optical effect lenses are available.

REFLECTOR:

Removable mirror-finish reflector to block up light and provide wider horizontal spread.

FASTENERS:

All fasteners are stainless steel.

WIRING:

Pre-wired with a fifteen-foot pigtail of 18-3 submersible cable.
Connectors for a required above-water connection are also included.

CAUTION:

Follow installation instructions as well as local electrical codes when installing.
NOT for use in swimming pools or spas.

LED:

Integrated LED Module.
2.5 – 5 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC.
Low voltage transformer required to operate (sold separately).

DIMENSIONS

