



**MODEL 4019** | Specification Sheet  
Residential Series • Path & Area

TYPE:  MODEL:

PROJECT:

**PRODUCT FEATURES**

Wattage	4.5 W or 5.5 W
Voltage	9 – 15 VAC
Lumens	295 or 389 Lumens
Lamp Type	MR-16 LED
Housing	Aluminum
Dimensions	10 3/4" D x 25 3/8" H



**ORDERING INFORMATION**

EXAMPLE: **ML-4019-B-4.5-W-36-FR**

MOUNTING	MODEL	FINISH	LED	ACCESSORIES
	4019			

MOUNTING	MODEL	FINISH	LED	ACCESSORIES
<b>ML</b> ABS Ground Stake <b>AC</b> Wall Mount Canopy	<b>4019</b>	<b>B</b> Black <b>Z</b> Architectural Bronze <b>DZ</b> Dark Bronze <b>GT</b> Granite <b>W</b> White	<b>BR</b> Architectural Brick <b>LZ</b> Light Bronze <b>SB</b> Special Bronze <b>GG</b> Glossy Gray <b>R</b> Rust <b>HG</b> Hunter Green <b>WB</b> Weathered Bronze <b>WI</b> Weathered Iron <b>GM</b> Graphite Metallic	<b>G</b> Verde <b>P</b> Pewter <b>M</b> Mocha <b>OF</b> Olde Finish

LED	ACCESSORIES	ORDERING NOTES
<b>4.5-W-15</b> 4.5 Watts   Warm   15° Narrow Spot <b>4.5-W-25</b> 4.5 Watts   Warm   25° Spot <b>4.5-W-36</b> 4.5 Watts   Warm   36° Flood <b>4.5-W-60</b> 4.5 Watts   Warm   60° Wide Flood <b>5.5-W-15</b> 5.5 Watts   Warm   15° Narrow Spot <b>5.5-W-25</b> 5.5 Watts   Warm   25° Spot <b>5.5-W-36</b> 5.5 Watts   Warm   36° Flood <b>5.5-W-60</b> 5.5 Watts   Warm   60° Wide Flood <b>NL</b> No Lamp	<b>FR</b> Frosted Lens <b>BL</b> Flat Cool Blue Lens <b>SL</b> Flat Spread Lens <b>DBL</b> Flat Dark Blue Lens <b>GL</b> Flat Dark Green Lens <b>RL</b> Flat Red Lens <b>YL</b> Flat Amber Lens <b>HL</b> Honeycomb louver <b>5</b> 5' Wire Lead	Fixtures shipped with specified mounting hardware.  Custom length stems available - Consult local distributor.



**PROFESSIONAL  
OUTDOOR LIGHTING**

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)  
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



**SPECIFICATIONS**

**HOUSING CONSTRUCTION:**

Die-cast A360 aluminum.

**STEM CONSTRUCTION:**

½" schedule-40 aluminum pipe.

**FINISH:**

Powder coat finish available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

**LENS:**

Clear, tempered glass lens.  
Optical effect lenses are available.

**AIMING:**

Adjustable multi-access swivel provides up to ±90° of tilt from vertical as well as 360° of full circle rotation in vertical & horizontal planes.

**MOUNTING:**

Bottom of stem threaded with ½" NPT.

**FASTENERS:**

All fasteners are stainless steel.

**WIRING:**

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

**CERTIFICATION:**

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

**LED:**

MR-16 LED Lamp.  
295 or 389 Lumens.  
4.5 or 5.5 Watts.

**ELECTRICAL:**

Input voltage range 9 - 15 VAC.  
Low voltage transformer required to operate (sold separately).

**LIGHT DISTRIBUTION:**

Very Narrow Spot **15** (15°)  
Narrow Spot **25** (25°)  
Medium Flood **36** (36°)  
Wide Flood **60** (60°)

**DIMENSIONS**

