



MODEL 5273 | Specification Sheet
Residential Series • In-Grade

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES



Wattage	4.5 W or 5.5 W
Voltage	9 – 15 VAC
Lumens	295 or 389 Lumens
Lamp Type	MR-16 LED
Housing	Injection-Molded Polymer
Dimensions	5" DIA x 6¼" D



ORDERING INFORMATION

EXAMPLE: **GW-5273-B-4.5-W-36**

CATEGORY	MODEL	FINISH	LED
	5273		

CATEGORY	MODEL	FINISH	LED	ORDERING NOTES
GW In-Grade	5273	B Black	4.5-W-15 4.5 Watts Warm 15° Narrow Spot	
CM In-Grade Conduit Mount		Z Architectural Bronze	4.5-W-25 4.5 Watts Warm 25° Spot	
		DZ Dark Bronze	4.5-W-36 4.5 Watts Warm 36° Flood	
		GT Granite	4.5-W-60 4.5 Watts Warm 60° Wide Flood	
		W White	5.5-W-15 5.5 Watts Warm 15° Narrow Spot	
		BR Architectural Brick	5.5-W-25 5.5 Watts Warm 25° Spot	
		LZ Light Bronze	5.5-W-36 5.5 Watts Warm 36° Flood	
		SB Special Bronze	5.5-W-60 5.5 Watts Warm 60° Wide Flood	
		GG Glossy Gray	NL No Lamp	
		R Rust		
		HG Hunter Green		
		WB Weathered Bronze		
		WI Weathered Iron		
		GM Graphite Metallic		
		G Verde		
		P Pewter		
		M Mocha		
		OF Olde Finish		



PROFESSIONAL
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

HOUSING CONSTRUCTION:

Injection-molded glass-reinforced polymer.

LENS COVER CONSTRUCTION:

Injection-molded glass-reinforced polymer.

FINISH:

Powder coat finish available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

LENS:

Clear, tempered glass lens.
Optical effect lenses are available.

MOUNTING:

In-grade. Mounting accessories not required.
Conduit mount fixtures have two 3/4" NPT inlets on bottom.
Optional concrete mounting kit available.

FASTENERS:

All fasteners are stainless steel.

WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

LED:

MR-16 LED Lamp.
295 or 389 Lumens.
4.5 or 5.5 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC.
Low voltage transformer required to operate (sold separately).

DIMENSIONS

