



MODEL 2146 | Specification Sheet
Residential Series • Brass & Copper • Step Light

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES



Wattage	1 – 5 W
Voltage	9 – 15 VAC
Faceplate	Brass, Copper or Stainless Steel
Dimensions	9 1/8" L x 2 7/8" H x 3 1/2" D

ORDERING INFORMATION

EXAMPLE: SL-2146-BSN-W-LC5ND

CATEGORY	MODEL	FINISH	LED
SL	2146		

CATEGORY	MODEL	FINISH	LED
SL Step Light	2146	BSN Natural Brass BSO Olde Brass CSN Natural Copper SS Stainless Steel	W-LC5ND 5 Watts Warm Integrated LED
			N-LC5ND 5 Watts Neutral Integrated LED
			C-LC5ND 5 Watts Cool Integrated LED
			2.5-W-G-T3 2.5 Watts Warm T3 LED Lamp
			150-W-G4 1.5 Watts Warm G4 LED Lamp (x 2)
			NL No Lamp





SPECIFICATIONS

HOUSING CONSTRUCTION:

Stamped & formed aluminum recessed box with 1/2" knockouts on the back & side.

COVER PLATE CONSTRUCTION:

Stamped solid brass, copper, or stainless steel.

LENS:

Translucent, high-impact polycarbonate lens.

MOUNTING:

Recessed mounting box included.

FASTENERS:

All fasteners are stainless steel.

WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

LED:

- Integrated LED Module. 5 Watts.
- G4 LED Lamp (x 2). 1.5 Watts (x 2).

ELECTRICAL:

Input voltage range 9 - 15 VAC.
Low voltage transformer required to operate (sold separately).

DIMENSIONS

