



MODEL 2120 | Specification Sheet
Residential Series • Up / Accent / Downlight

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES



| | |
|------------|---------------------------|
| Wattage | 4.5 W or 5.5 W |
| Voltage | 9 – 15 VAC |
| Lumens | 295 or 389 Lumens |
| Lamp Type | MR-16 LED |
| Housing | Copper or Stainless Steel |
| Dimensions | 2 1/8" DIA x 5 1/2" D |

ORDERING INFORMATION

EXAMPLE: GR-2120-CSN-4.5-W-36-FR

| CATEGORY | MODEL | FINISH | LED |
|----------|-------|--------|-----|
| | 2120 | | |

| CATEGORY | MODEL | FINISH | LED | ACCESSORIES |
|-----------------------------|-------------|---------------------------|--|---|
| GR ABS Ground Stake | 2120 | CSN Natural Copper | 4.5-W-15 4.5 Watts Warm 15° Narrow Spot | BL Flat Cool Blue Lens SL Flat Spread Lens DBL Flat Dark Blue Lens GL Flat Dark Green Lens RL Flat Red Lens YL Flat Amber Lens HL Honeycomb louver |
| WR Wall-Mount Canopy | | | 4.5-W-25 4.5 Watts Warm 25° Spot | |
| | | SS Stainless Steel | 4.5-W-36 4.5 Watts Warm 36° Flood | |
| | | | 4.5-W-60 4.5 Watts Warm 60° Wide Flood | |
| | | | 5.5-W-15 5.5 Watts Warm 15° Narrow Spot | |
| | | | 5.5-W-25 5.5 Watts Warm 25° Spot | |
| | | | 5.5-W-36 5.5 Watts Warm 36° Flood | |
| | | | 5.5-W-60 5.5 Watts Warm 60° Wide Flood | |
| | | | NL No Lamp | |



**PROFESSIONAL
OUTDOOR LIGHTING**

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

CONSTRUCTION:

Heavy-gauge, extruded, copper or stainless steel with machined brass base.

LENS:

Clear, tempered glass lens.
Optical effect lenses are available.

MOUNTING:

Solid Brass knuckle with 1/2" NPS thread.

FASTENERS/INSERTS:

Fasteners are stainless steel and brass.

WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

LED:

MR-16 LED Lamp.
295 or 389 Lumens.
4.5 or 5.5 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC.
Low voltage transformer required to operate (sold separately).

DIMENSIONS

