




5280 Composite | 50 W max (halogen) | MR-16 Lamp or LED | LN-20 BAB/FG Std



5281 Composite | 50 W max (halogen) | MR-16 Lamp or LED | LN-20 BAB/FG Std



5282 Composite | 50 W max (hal.) | MR-16 Lamp or LED | LN-20 BAB/FG Std



**HOUSING/LENS COVER**

- » Injection-molded, reinforced polymer
- » Formulated for most Vista polyester powder-coated finishes
- » Exceptional strength and UV stability
- » Silicone O-ring gasket
- » Superior weather-tight seal
- » Ingress protection rating of IP67
- » Suspended in 6" ABS well

**FINISH**

- » Polyester powder-coated finish. See ordering information for available colors.

**SOCKET/LAMP HOLDER**

- » Proprietary ceramic socket
- » Nickel contacts
- » Stainless steel springs
- » Teflon-jacketed wire leads

**LENS**

- » Convex
- » Clear
- » Tempered
- » Shock- and heat-resistant
- » Soda-lime glass
- » For optical effect lenses, see ordering information.

**OPTICS/AIMING**

- » Adjustable and lockable lamp bracket
- » ±25° of tilt
- » 360° rotation of housing
- » ±45° of tilt with housing bracket

**LAMP TYPE**

- » Standard lamp included with fixture. For other lamp and wattage options see Lamp Guide, pages 128-130.

**PHOTOMETRICS**

- » For photometric data, see pages 131-149.

**MOUNTING**

- » In-grade

**FASTENERS**

- » Stainless steel fasteners

**WIRING**

- » Prewired with a three-foot pigtail of 18-2 direct-burial cable and underground connectors for a secure connection to the supply cable.

**LED SPECIFICATIONS** Look for this mark on products where LED options are available.

**LED Lamp**

High Output Plug-in LED lamp with Vista exclusive smart-driver, powered to operate for 30,000 hours with an operating voltage of 9-15 VAC. See page 128 for extended specifications and options.

**Integrated LED**

High Output LED lamp assembly with Vista exclusive smart-driver, powered to operate for 50,000 hours with an operating voltage of 9-15 VAC. See page 130 for extended specifications and options.

**ORDERING INFORMATION** Select appropriate choice from each column

example: GW-5281-B-BAB/FG-CBL

Mounting	No.	Finish	Lamp	Lenses/Accessories
GW In-grade	5280 5281 5282	B Black DZ Dark Bronze LZ Light Bronze SB Special Bronze G Verde P Pewter BR Architectural Brick GT Granite TC Terracotta R Rust HG Hunter Green M Mocha WB Weathered Bronze WI Weathered Iron W White	<b>LAMP</b> See reference codes, pages 128-130  <b>INTEGRATED LED</b> See reference codes, page 130, group F	CBL Convex Cool-Blue Lens CFR Convex Frosted Lens SL Flat Spread Lens DBL Flat Dark Blue Lens GL Flat Dark Green Lens RL Flat Red Lens YL Flat Amber Lens  HL Honeycomb Louver DL Directional Grate Cover BD Bi-directional Grate Cover

**NOTE:** not all accessories are available for all fixtures. See footnotes below before ordering. Fixtures shipped with standard lamp, unless otherwise specified, and with specified mounting hardware.

