



TYPE: MODEL:
PROJECT:

PRODUCT DESCRIPTION

5006 Uplight	Qty 6
2265 Pathlight	Qty 4
GS-150 ABS Ground Stake	Qty 10
DK-250 Photocell controlled 12V Transformer & Stand (250 W)	Qty 1
Rolling Demonstration Case with Handle	Qty 1
12' Low Voltage Cable w/ Quick Connect	Qty 4
75' Low-Voltage Cable w/ Quick Connect	Qty 1
Low Voltage 4-way Quick-Connect/Splitter	Qty 4
Photocell Cap	Qty 1
Brass Thumbscrews (for securing transformer stand legs)	Qty 3



DEMO CASE FEATURES

Housing	Polypropylene
Latches	Metal Front and Side Latches
Handles	Carry Handle plus Telescopic Handle
Security	Padlockable Hasps on Side Latches
Dimensions	24 3/4" H x 18 1/2" W x 11" D





5006 FEATURES



LED Type	4.5W - 36° LED MR-16
Voltage	9 – 15 VAC
Lumens	295 Lumens
Housing	Die-cast A360 Aluminum
Finish	Bronze Powder Coat Finish
Lens	Clear Tempered Glass
Mounting	Injection-molded composite knuckle with ½" NPS thread
Dimensions	2 5/8" DIA x 5 3/4" D



2265 FEATURES



LED Type	1.1W T3 Bi-Pin
Voltage	9 – 15 VAC
Housing	Die-cast A360 Aluminum
Finish	Bronze Powder Coat Finish
Lens	Clear Polycarbonate
Mounting	Bottom of stem threaded with ½" NPT
Dimensions	4" DIA x 15 7/8" H





DK-250 FEATURES



Wattage	250 W
Primary Voltage	120 VAC
Secondary Voltage	12 VAC
Housing	Stainless Steel
Finish	Black Powder Coat Finish



GS-150 FEATURES



Type	Ground Stake
Material	ABS
Fixture Mounting	1/2" FPT Base
Dimensions	9" H x 2 3/8" DIA

