



**MODEL 4245** | Specification Sheet  
Residential Series • Step Light

TYPE:  MODEL:

PROJECT:

**PRODUCT FEATURES**



Wattage	1 – 5 W
Voltage	9 – 15 VAC
Housing	Aluminum
Dimensions	9 1/8" L x 2 7/8" H x 3 1/2" D



**ORDERING INFORMATION**

EXAMPLE: *SL-4245-B-W-LC5ND*

CATEGORY	MODEL	FINISH	LED
SL	4245		

CATEGORY	MODEL	FINISH	LED
SL Step Light	4245	<b>B</b> Black	<b>W-LC5ND</b> 5 Watts   Warm   Integrated LED
		<b>Z</b> Architectural Bronze	<b>N-LC5ND</b> 5 Watts   Neutral   Integrated LED
		<b>DZ</b> Dark Bronze	<b>C-LC5ND</b> 5 Watts   Cool   Integrated LED
		<b>GT</b> Granite	<b>150-W-G4</b> 1.5 Watts   Warm   G4 LED Lamp (x 2)
		<b>W</b> White	<b>NL</b> No Lamp
		<b>BR</b> Architectural Brick	
		<b>LZ</b> Light Bronze	
		<b>SB</b> Special Bronze	
		<b>GG</b> Glossy Gray	
		<b>R</b> Rust	
		<b>HG</b> Hunter Green	
		<b>WB</b> Weathered Bronze	
		<b>WI</b> Weathered Iron	
		<b>GM</b> Graphite Metallic	
		<b>G</b> Verde	
<b>P</b> Pewter			
<b>M</b> Mocha			
<b>OF</b> Olde Finish			



**PROFESSIONAL  
OUTDOOR LIGHTING**

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)  
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



### SPECIFICATIONS

**HOUSING CONSTRUCTION:**

Stamped & formed aluminum recessed box with 1/2" knockouts on the back & side.

**COVER PLATE CONSTRUCTION:**

Die-cast A360 aluminum.

**FINISH:**

Powder coat finish for Aluminum Door Cover available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

**LENS:**

Translucent, high-impact polycarbonate lens.

**MOUNTING:**

Recessed mounting box included.

**FASTENERS:**

All fasteners are stainless steel.

**WIRING:**

Provided with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

**CERTIFICATION:**

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

**LED:**

- Integrated LED Module. 5 Watts.
- G4 LED Lamp (x 2). 1.5 Watts (x 2).

**ELECTRICAL:**

Input voltage range 9 - 15 VAC.  
Low voltage transformer required to operate (sold separately).

### DIMENSIONS

