



MODEL 4018 | Specification Sheet
Residential Series • Specialty • Deck Light

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES



Wattage	5 W
Voltage	9 – 15 VAC
Housing	Aluminum
Dimensions	7" W x 1 3/4" D x 44 1/8" L



ORDERING INFORMATION

EXAMPLE: **FL-4018-N-W-LC5ND**

CATEGORY	MODEL	FINISH	LED
FL	4018	N	

CATEGORY	MODEL	FINISH	LED
FL Flexible Stem Deck Light	4018	N Nickel	W-LC5ND 5 Watts Warm Integrated LED N-LC5ND 5 Watts Neutral Integrated LED C-LC5ND 5 Watts Cool Integrated LED



**PROFESSIONAL
OUTDOOR LIGHTING**

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

HOUSING CONSTRUCTION:

Stamped and brushed 20-gauge 304 stainless steel.

STEM CONSTRUCTION:

Heavy gauge, adjustable, nickel plated stainless steel tubing.

LENS:

Frosted, high-impact polycarbonate lens.

MOUNTING:

Bottom of stem threaded into CNC-machined solid aluminum mounting canopy.

FASTENERS/INSERTS:

All fasteners are stainless steel.

WIRING:

Prewired with a 36" pigtail of 18-2 SPT1 UV resistant cable and watertight connectors.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

LED:

Integrated LED Module. 5 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC.

Low voltage transformer required to operate (sold separately).

DIMENSIONS

