



MODEL 2138 | Specification Sheet
Residential Series • Bollard

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES



Wattage	4.5 W or 5.5 W
Voltage	9 – 15 VAC
Lumens	295 or 389 Lumens
Lamp Type	MR-16 LED
Housing	Copper or Stainless Steel
Dimensions	2 1/8" DIA x 16" H

ORDERING INFORMATION

EXAMPLE: **BR-2138-B-4.5-W-36**

MOUNTING **MODEL** **FINISH** **LED**
BR 2138

MOUNTING	MODEL	FINISH	LED	ORDERING NOTES
BR Ground & Concrete Mounting Kit	2138	CSN Natural Copper SS Stainless Steel	4.5-W-15 4.5 Watts Warm 15° Narrow Spot	Fixtures shipped with specified mounting hardware.
			4.5-W-25 4.5 Watts Warm 25° Spot	
			4.5-W-36 4.5 Watts Warm 36° Flood	
			4.5-W-60 4.5 Watts Warm 60° Wide Flood	
			5.5-W-15 5.5 Watts Warm 15° Narrow Spot	
			5.5-W-25 5.5 Watts Warm 25° Spot	
			5.5-W-36 5.5 Watts Warm 36° Flood	
			5.5-W-60 5.5 Watts Warm 60° Wide Flood	
			NL No Lamp	



PROFESSIONAL OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

CONSTRUCTION:

Heavy-gauge, extruded, copper or stainless steel post fitted with machined solid brass cap.

LENS:

Clear, machined acrylic lens.

MOUNTING:

Aluminum mounting base with ABS ground stake included.

FASTENERS:

All fasteners are stainless steel.

WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

LED:

MR-16 LED Lamp.
295 or 389 Lumens.
4.5 or 5.5 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC.
Low voltage transformer required to operate (sold separately).

DIMENSIONS

