



**MODEL 2132** | Specification Sheet  
Residential Series • Brass & Copper • Path & Area

TYPE:  MODEL:

PROJECT:

**PRODUCT FEATURES**



Wattage	1 – 5 W
Voltage	9 – 15 VAC
Housing	Copper or Brass
Dimensions	5 ½" DIA x 13 ¼" H (CSN) 5 ½" DIA x 17 ½" H (BSN, BSO)

**ORDERING INFORMATION**

EXAMPLE: *PR-2132-BSN-W-LB5ND*

**MOUNTING**                      **MODEL**                      **FINISH**                      **LED**  
PR                                      2132                                      BSN

MOUNTING	MODEL	FINISH	LED
PR ABS Ground Stake	2132	CSN Natural Copper	W-LB2ND 2.5 Watts   Warm   Integrated LED
		BSN Natural Brass	N-LB2ND 2.5 Watts   Neutral   Integrated LED
		BSO Olde Brass	C-LB2ND 2.5 Watts   Cool   Integrated LED
		W-LB5ND 5 Watts   Warm   Integrated LED	
		N-LB5ND 5 Watts   Neutral   Integrated LED	
		C-LB5ND 5 Watts   Cool   Integrated LED	
		150-W-G4 1.5 Watts   Warm   G4 LED Lamp	
NL No Lamp			



**PROFESSIONAL  
OUTDOOR LIGHTING**

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)  
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



**SPECIFICATIONS**

**HOUSING CONSTRUCTION:**

Solid Copper or Brass shade.  
Twist-To-Lock Solid Brass lamp base.

**STEM CONSTRUCTION:**

1/2" Solid Copper or Brass pipe.

**FINISH:**

Brushed Natural Copper, Natural Brass or Olde Brass finish.  
(Brushed copper will rapidly age to an elegant rich bronze-like color and may develop areas of patina over time.)

**LENS:**

Textured, high-impact polycarbonate lens.

**MOUNTING:**

Bottom of stem threaded with 1/2" NPT.

**FASTENERS:**

All fasteners are stainless steel.

**WIRING:**

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

**CERTIFICATION:**

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

**LED:**

- Integrated LED Module. 2.5 – 5 Watts.
- G4 LED Lamp. 1.5 Watts.

**ELECTRICAL:**

Input voltage range 9 - 15 VAC.  
Low voltage transformer required to operate (sold separately).

**DIMENSIONS**

