



**MODEL 2116** | Specification Sheet  
Residential Series • Up / Accent / Downlight

TYPE:  MODEL:

PROJECT:

**PRODUCT FEATURES**



Wattage	4.5 W or 5.5 W
Voltage	9 – 15 VAC
Lumens	295 or 389 Lumens
Lamp Type	MR-16 LED
Housing	Copper or Stainless Steel
Dimensions	2 1/8" DIA x 7 3/8" D

**ORDERING INFORMATION**

EXAMPLE: GR-2116-CSN-4.5-W-36-FR

CATEGORY	MODEL	FINISH	LED
	2116		

CATEGORY	MODEL	FINISH	LED	ACCESSORIES
<b>GR</b> ABS Ground Stake	<b>2116</b>	<b>CSN</b> Natural Copper	<b>4.5-W-15</b> 4.5 Watts   Warm   15° Narrow Spot	<b>BL</b> Flat Cool Blue Lens <b>SL</b> Flat Spread Lens <b>DBL</b> Flat Dark Blue Lens <b>GL</b> Flat Dark Green Lens <b>RL</b> Flat Red Lens <b>YL</b> Flat Amber Lens <b>HL</b> Honeycomb louver
<b>WR</b> Wall-Mount Canopy			<b>4.5-W-25</b> 4.5 Watts   Warm   25° Spot	
		<b>SS</b> Stainless Steel	<b>4.5-W-36</b> 4.5 Watts   Warm   36° Flood	
			<b>4.5-W-60</b> 4.5 Watts   Warm   60° Wide Flood	
			<b>5.5-W-15</b> 5.5 Watts   Warm   15° Narrow Spot	
			<b>5.5-W-25</b> 5.5 Watts   Warm   25° Spot	
			<b>5.5-W-36</b> 5.5 Watts   Warm   36° Flood	
			<b>5.5-W-60</b> 5.5 Watts   Warm   60° Wide Flood	
			<b>NL</b> No Lamp	



PROFESSIONAL  
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)  
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



## SPECIFICATIONS

### CONSTRUCTION:

Heavy-gauge, extruded, copper or stainless steel with machined brass base.

### LENS:

Clear, tempered glass lens.  
Optical effect lenses are available.

### MOUNTING:

Solid Brass knuckle with 1/2" NPS thread.

### FASTENERS/INSERTS:

Fasteners are stainless steel and brass.

### WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

### CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

### LED:

MR-16 LED Lamp.  
295 or 389 Lumens.  
4.5 or 5.5 Watts.

### ELECTRICAL:

Input voltage range 9 - 15 VAC.  
Low voltage transformer required to operate (sold separately).

## DIMENSIONS

