



**MODEL 2148** | Specification Sheet  
Residential Series • Brass & Copper • Step Light

TYPE:  MODEL:

PROJECT:

**PRODUCT FEATURES**



Wattage	4.5 W or 5.5 W
Voltage	9 – 15 VAC
Lumens	295 or 389 Lumens
Lamp Type	MR-16 LED
Housing	Injection-Molded Polymer
Dimensions	5" DIA x 6¼" D

**ORDERING INFORMATION**

EXAMPLE: *SL-2148-BSN-4.5-W-36-CFR*

MOUNTING	MODEL	FINISH	LED	ACCESSORIES
SL	2148			

MOUNTING	MODEL	FINISH	LED	ACCESSORIES
SL Step Light	2148	<b>BSN</b> Natural Brass <b>BSO</b> Olde Brass <b>SS</b> Stainless Steel	<b>4.5-W-15</b> 4.5 Watts   Warm   15° Narrow Spot	<b>CFR</b> Crowned Frosted Lens <b>CBL</b> Crowned Cool Blue Lens <b>SL</b> Flat Spread Lens <b>DBL</b> Flat Dark Blue Lens <b>GL</b> Flat Dark Green Lens <b>RL</b> Flat Red Lens <b>YL</b> Flat Amber Lens <b>HL</b> Honeycomb louver
			<b>4.5-W-25</b> 4.5 Watts   Warm   25° Spot	
			<b>4.5-W-36</b> 4.5 Watts   Warm   36° Flood	
			<b>4.5-W-60</b> 4.5 Watts   Warm   60° Wide Flood	
			<b>5.5-W-15</b> 5.5 Watts   Warm   15° Narrow Spot	
			<b>5.5-W-25</b> 5.5 Watts   Warm   25° Spot	
			<b>5.5-W-36</b> 5.5 Watts   Warm   36° Flood	
			<b>5.5-W-60</b> 5.5 Watts   Warm   60° Wide Flood	
			<b>NL</b> No Lamp	



**PROFESSIONAL  
OUTDOOR LIGHTING**

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)  
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



**SPECIFICATIONS**

**HOUSING CONSTRUCTION:**

Injection-molded glass-reinforced polymer.

**LENS COVER CONSTRUCTION:**

Machined Brass or 304 Stainless Steel.

**FINISH:**

Natural Brass, Olde Brass or Natural Stainless Steel lens cover.  
Housing available in black only.

**LENS:**

Frosted, tempered glass lens.  
Optical effect lenses are available.

**MOUNTING:**

Recessed mounting box has two 1/2" NPT inlets.  
Optional concrete mounting kit available.

**FASTENERS:**

All fasteners are stainless steel.

**WIRING:**

Provided with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

**CERTIFICATION:**

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

**LED:**

MR-16 LED Lamp.  
295 or 389 Lumens.  
4.5 or 5.5 Watts.

**ELECTRICAL:**

Input voltage range 9 - 15 VAC.  
Low voltage transformer required to operate (sold separately).

**LIGHT DISTRIBUTION:**

Very Narrow Spot **15** (15°)  
Narrow Spot **25** (25°)  
Medium Flood **36** (36°)  
Wide Flood **60** (60°)

**DIMENSIONS**

