



MODEL **5013i** CC | Specification Sheet
Residential Series • chroma **connect**

TYPE: MODEL:
PROJECT:

PRODUCT FEATURES



Wattage	6 W
Voltage	11 – 18 VAC
Lumens	110 – 450 Lumens
Distribution	38° (MF)
CCT	2200 K – 5700 K CCT White
CRI	80 CRI min.
Wireless Control	VistaPro Smart App with Bluetooth Mesh Technology
Housing	Die-cast Aluminum
Dimensions	2 1/8" DIA x 5 1/4" D



ORDERING INFORMATION

EXAMPLE: GR-5013i-B-6-RGBW-38-FR

MOUNTING	MODEL	FINISH	WATTAGE	COLOR	DISTRIBUTION	ACCESSORIES
	5013i		6	RGBW	38	

MOUNTING	MODEL	FINISH			
GR ABS ground stake WR Wall-mount canopy TR Tree-mount junction box	5013i	B Black Z Architectural Bronze DZ Dark Bronze GT Granite W White	BR Architectural Brick LZ Light Bronze SB Special Bronze GG Glossy Gray R Rust HG Hunter Green WB Weathered Bronze WI Weathered Iron GM Graphite Metallic	G Verde P Pewter M Mocha OF Olde Finish	
WATTAGE	COLOR	DISTRIBUTION	ACCESSORIES	ORDERING NOTES	
6 6 Watts	RGBW RGB Color Options + Tunable White	38 38° Flood	FR Frosted Lens 5 5' Wire Lead	Fixtures shipped with specified mounting hardware. If fixture is to be used in conjunction with Extended Arm Mount (EAM): Must specify with extended wire length	



PROFESSIONAL
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

HOUSING CONSTRUCTION:

Die-cast A360 aluminum. Optic and driver compartment environmentally sealed.

FINISH:

Powder coat finish available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish. Custom Powder coat finishes available on request.

LENS:

Clear, tempered glass lens.

FASTENERS:

All fasteners are stainless steel.

WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

MOUNTING:

Injection-molded composite knuckle with 1/2" NPS thread.

WATTAGE:

6 Watts.

INPUT VOLTAGE:

11 - 18 VAC / 60 Hz.

COLOR:

RGBW

COLOR TEMPERATURE:

2200 K – 5700 K CCT White.

LUMINOSITY:

110 lm – 450 lm.

COLOR RENDERING INDEX (CRI):

80

MINIMUM RATED LIFE:

40,000 Hrs.

BEAM SPREAD:

38°

DIMMING:

Yes

WIRELESS CONTROL:

VistaPro Smart App with Bluetooth Mesh Technology.
Android and iOS compatible.

DIMENSIONS

