



MODEL **8242** | Specification Sheet  
Residential Series • Bollard

TYPE:

MODEL:

PROJECT:

PRODUCT FEATURES

Wattage	3 W (1.5 W x 2)
Voltage	9 – 15 VAC
Lamp Type	G4 LED
Housing	Aluminum
Dimensions	18" W x 25 7⁄8" H (above grade)   37 7⁄8" H (over all)



ORDERING INFORMATION

EXAMPLE: **PR-8242-B-150-W-G4-RS**

MOUNTING	MODEL	FINISH	LED
BR	8242		

MOUNTING	MODEL	FINISH	LED
BR Direct-burial Post	8242	<b>B</b> Black	<b>150-W-G4</b> 1.5 Watts   Warm   G4 LED Lamp (x 2) <b>NL</b> No Lamp
		<b>Z</b> Architectural Bronze	
		<b>DZ</b> Dark Bronze	
		<b>GT</b> Granite	
		<b>W</b> White	
		<b>BR</b> Architectural Brick	
		<b>LZ</b> Light Bronze	
		<b>SB</b> Special Bronze	
		<b>GG</b> Glossy Gray	
		<b>R</b> Rust	
		<b>HG</b> Hunter Green	
		<b>WB</b> Weathered Bronze	
		<b>WI</b> Weathered Iron	
		<b>GM</b> Graphite Metallic	
		<b>G</b> Verde	
		<b>P</b> Pewter	
		<b>M</b> Mocha	
		<b>OF</b> Olde Finish	



PROFESSIONAL  
OUTDOOR LIGHTING



## SPECIFICATIONS

### HOUSING CONSTRUCTION:

Die-cast A360 aluminum.

### POST CONSTRUCTION:

Extruded Aluminum (1/8" wall thickness).

### FINISH:

Powder coat finish available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

### LENS:

Clear, high-impact polycarbonate lens.

### MOUNTING:

Direct-burial Post. (Post extended 12" for in-ground or concrete mounting.)

### FASTENERS:

All fasteners are stainless steel.

### WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

### CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

### LED:

G4 LED Lamp (x 2).

1.5 Watts (x 2).

### ELECTRICAL:

Input voltage range 9 - 15 VAC.

Low voltage transformer required to operate (sold separately).

## DIMENSIONS

