


TYPE:	MODEL:
PROJECT:	

## **PRODUCT FEATURES**

Wattage	1 – 5 W
Voltage	9 – 15 VAC
Housing	Aluminum
Dimensions	4¼" DIA x6¼" H



EXAMPLE: HT-4216-B-W-LB5ND

# **ORDERING INFORMATION**

CATEGORY MODEL FINISH LED
HT 4216

CATEGORY	MODEL	FINIS	SH	LED	
HT Hanging Downlight	4216	В	Black	W-LB2ND	2.5 Watts   Warm   Integrated LED
		z	Architectural Bronze	N-LB2ND	2.5 Watts   Neutral   Integrated LED
		DZ	Dark Bronze	C-LB2ND	2.5 Watts   Cool   Integrated LED
		GT	Granite	W-LB5ND	5 Watts   Warm   Integrated LED
		w	White	N-LB5ND	5 Watts   Neutral   Integrated LED
		BR	Architectural Brick	C-LB5ND	5 Watts   Cool   Integrated LED
		LZ	Light Bronze	150-W-G4	1.5 Watts   Warm   G4 LED Lamp
		SB	Special Bronze		
		GG	Glossy Gray	NL	No Lamp
		R	Rust		
		НG	Hunter Green		
		WВ	Weathered Bronze		
		wı	Weathered Iron		
		GM	Graphite Metallic		
		G	Verde		
		P	Pewter		
		м	Mocha		
		OF	Olde Finish		



### **SPECIFICATIONS**

### **HOUSING CONSTRUCTION:**

Die-cast A360 aluminum.

### FINISH:

Powder coat finish available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

#### LENS:

Clear, high-impact polycarbonate lens.

### MOUNTING:

Solid brass loop with a six-foot stainless steel cable-hanger included.

#### **FASTENERS:**

All fasteners are stainless steel.

# LED:

- Integrated LED Module. 2.5 5 Watts.
- G4 LED Lamp. 1.5 Watts.

### **ELECTRICAL:**

Input voltage range 9 - 15 VAC.

Low voltage transformer required to operate (sold separately).

### WIRING:

Prewired with a 36" pigtail of 18-2 SPT1 UV resistant cable and watertight connectors.

## **CERTIFICATION:**

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

# **DIMENSIONS**

