




2238 Aluminum | 35 W max (halogen) | MR-16 Lamp or LED | LN-20 BAB Std




4210 Aluminum | 20 W max (halogen) | T3 Lamp or LED | LN-10 T3 Std



7213 Aluminum | 20 W max (halogen) | T3 Lamp or LED | LN-10 T3 Std



9240 Aluminum | 20 W max (halogen) | T3 Lamp or LED | LN-10 T3 Std



	LENS
2238	<ul style="list-style-type: none"> » Clear » Tempered » Shock- and heat-resistant » Soda-lime glass » For optical effect lenses, see ordering information.
4210	<ul style="list-style-type: none"> » Clear » High impact polycarbonate
7213	<ul style="list-style-type: none"> » Clear » High impact polycarbonate
9240	<ul style="list-style-type: none"> » Clear » High impact polycarbonate

HOUSING
<ul style="list-style-type: none"> » Die-cast » Copper-free aluminum
FINISH
<ul style="list-style-type: none"> » Polyester powder-coated finish. See ordering information for available colors.
SOCKET/LAMP HOLDER
<ul style="list-style-type: none"> » Proprietary ceramic socket » Nickel contacts » Stainless steel springs » Teflon-jacketed wire leads
LAMP TYPE
<ul style="list-style-type: none"> » Standard lamp included with fixture. For other lamp and wattage options see Lamp Guide, pages 128-130.
PHOTOMETRICS
<ul style="list-style-type: none"> » For photometric data, see pages 131-149.
MOUNTING
<ul style="list-style-type: none"> » Solid brass hanging loop » Six-foot stainless steel cable hanger
FASTENERS
<ul style="list-style-type: none"> » Stainless steel fasteners
WIRING
<ul style="list-style-type: none"> » Prewired with a three-foot pigtail of 18-2 SPT1 UV-resistant cable and weather resistant connectors for a secure connection to the supply cable.

LED SPECIFICATIONS Look for this mark on products where LED options are available.

LED Lamp	Integrated LED
High Output Plug-in LED lamp with Vista exclusive smart-driver, powered to operate for 30,000 hours with an operating voltage of 9-15 VAC. See page 128 for extended specifications and options.	High Output LED lamp assembly with Vista exclusive smart-driver, powered to operate for 50,000 hours with an operating voltage of 9-15 VAC. See page 130 for extended specifications and options.

ORDERING INFORMATION Select appropriate choice from each column example: HT-4210-B-10 T3

Mounting	No.	Finish	Lamp	Lenses/Accessories
HT Brass loop with stainless steel cable hanger	2238 4210 7213 9240	B Black Z Architectural Bronze DZ Dark Bronze LZ Light Bronze SB Special Bronze G Verde P Pewter BR Architectural Brick GT Granite TC Terracotta R Rust HG Hunter Green M Mocha WB Weathered Bronze WI Weathered Iron W White	LAMP See reference codes, pages 128-130 INTEGRATED LED See reference codes, page 130, group B	FR Flat Frosted Lens BL Flat Cool Blue Lens * SL Flat Spread Lens * CX Convex Clear Lens * CFR Convex Frosted Lens * DBL Flat Dark Blue Lens * GL Flat Dark Green Lens * RL Flat Red Lens * YL Flat Amber Lens * HL Honeycomb Louver *

NOTE: not all accessories are available for all fixtures. See footnotes below before ordering.
 * Available for 2238 only.
 Fixtures shipped with standard lamp, unless otherwise specified, and with specified mounting hardware.