



MODEL 2101 | Specification Sheet
Residential Series • Up / Accent / Downlight

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES



Wattage	2.5 W
Voltage	9 – 15 VAC
Lumens	200 Lumens
Lamp Type	MR-11 LED
Housing	Solid Brass
Dimensions	1 3/4" DIA x 4 1/2" D



ORDERING INFORMATION

EXAMPLE: GR-2101-BSO-2.5-W-36-FR

MOUNTING	MODEL	FINISH	LED	ACCESSORIES
	2101	BSO		

MOUNTING	MODEL	FINISH	LED	ACCESSORIES
GR ABS Ground Stake WR Wall-Mount Canopy TR Tree-Mount Junction Box	2101	BSO Olde Brass	2.5-W-15 2.5 Watts Warm 15° Narrow Spot 2.5-W-25 2.5 Watts Warm 25° Spot 2.5-W-36 2.5 Watts Warm 36° Flood 2.5-W-60 2.5 Watts Warm 60° Wide Flood NL No Lamp	FR Frosted Lens BL Flat Cool Blue Lens SL Flat Spread Lens DBL Flat Dark Blue Lens GL Flat Dark Green Lens RL Flat Red Lens YL Flat Amber Lens HL Honeycomb louver 5 5' Wire Lead
				ORDERING NOTES Fixtures shipped with specified mounting hardware. If fixture is to be used in conjunction with Extended Arm Mount (EAM): Must specify with extended wire length



PROFESSIONAL
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

HOUSING CONSTRUCTION:

Heavy-gauge, extruded brass with machined brass base.

FINISH:

Olde Brass.

LENS:

Clear, tempered glass lens.
Optical effect lenses are available.

MOUNTING:

Injection-molded composite knuckle with 1/2" NPS thread.

FASTENERS/INSERTS:

Fasteners are stainless steel and brass.

WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

LED:

MR-11 LED Lamp.
200 Lumens.
2.5 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC.
Low voltage transformer required to operate (sold separately).

LIGHT DISTRIBUTION:

Very Narrow Spot **15** (15°)
Narrow Spot **25** (25°)
Medium Flood **36** (36°)
Wide Flood **60** (60°)

DIMENSIONS

