



WARNING: Junction box must be installed and grounded in accordance with the National Electrical Code (NEC) and local codes. Failure to do so may result in serious injury and/or damage to the junction box or attached luminaire.

SAFETY WARNING: Luminaire can become hot depending on lamp wattage. Lens and housing around lamp can become hot enough to blister hands. Particular care should be taken not to locate luminaires where small children can reach them if high wattage lamps are used.

NOTE: Always use UL recognized wire connectors for connections.

NOTE: Save these instructions for future reference.

JUNCTION BOX IS UL LISTED FOR ABOVE GRADE INSTALLATION ONLY.



TREE MOUNT INSTALLATION

- Place Tree Mount Box at desired location on tree with mounting hub always oriented toward the top.
- Using a drill, mark pilot holes by inserting drill bit through each mounting hole of junction box.
- 3. Drill pilot holes to approximately 1" depth to ease installation of lag bolts (provided).
- 4. Thread one hex nut (provided) on each lag bolt. Insert lag bolts (wood screw side) in pilot holes and tighten using a 7/6" wrench.
- 5. Place box on tree lining up mounting holes to lag bolts.
- 6. Install remaining two (2) hex nuts on lag bolts to lock in place.

NOTE: Hex nuts may be adjusted to accommodate future tree growth as well as angle adjustment of junction box.

- Secure conduit (by others) to bottom ½" NPT fitting, using a UL/CN Listed ½" NPT fitting connector, and feed wires through.
- 8. Attach green ground wire to green ground screw terminal.
- 9. Thread luminaire into $\frac{1}{2}$ " NPT fitting and secure with Allen screw (provided) at desired location.
- Attach luminaire leads to circuit leads observing polarity, black to black, white to white and green to ground.
- 11. Insert all wires into box and secure front cover using gasket (provided) and two (2) Phillips head screws (provided).
- 12. Supply power to junction box and check for proper operation.



