7223



Aluminum 20 W max (halogen)

T3 Lamp or LED

LN-10 T3 Std





Aluminum

20 W max (halogen)

T3 Lamp or LED

LN-10 T3 Std




Aluminum


7216

20 W max (halogen)

T3 Lamp or LED

LN-10 T3 Std





## HOUSING

- » Die-cast
- » Copper-free aluminum

# STEM

- » ½" Pipe
- » Schedule 40 aluminum

# FINISH

» Polyester powder-coated finish. See ordering information for available colors.

#### SOCKET/LAMP HOLDER

- » Proprietary ceramic socket
- » Nickel contacts
- » Stainless steel springs
- » Teflon-jacketed wire leads

#### LENS

- » Prismatic spread lens
- » High impact polycarbonate

# LAMP TYPE

» Standard lamp included with fixture. For other lamp and wattage options see Lamp Guide, pages 128-130.

# PHOTOMETRICS

» For photometric data, see pages 131-149.

#### MOUNTING

- » Bottom of stem threaded with ½" NPT
- » Fixture may be mounted into threaded hubs in junction boxes, ground stakes, or mounting canopies.
- See ordering information for mounting options. For optional mounting accessories, see pages 126-127.

### **FASTENERS**

» Stainless steel fasteners

#### WIRING

» Prewired with a three-foot pigtail of 18-2 direct-burial cable and underground connectors for a secure connection to the





Aluminum

20 W max (halogen)

T3 Lamp or LED

LN-10 T3 Std



Aluminum

20 W max (halogen)

T3 Lamp or LED LN-10 T3 Std



Aluminum

20 W max (halogen)

T3 Lamp or LED

LN-10 T3 Std




Aluminum

20 W max (halogen)

T3 Lamp or LED

LN-10 T3 Std



example: PR-6223-B-10 T3

Lenses/Accessories

FR Flat Frosted Lens

LED SPECIFICATIONS Look for this mark on products where LED options are available.

WB Weathered Bronze

WI Weathered Iron

W White

#### LED Lamp

to operate for 30,000 hours with an operating voltage of 9-15 VAC. See page 128 for extended specifications and options.

Integrated LED

High Output Plug-in LED lamp with Vista exclusive smart-driver, powered High Output LED lamp assembly with Vista exclusive smart-driver, powered to operate for 50,000 hours with an operating voltage of 9-15 VAC. See page 130 for extended specifications and options.

# ORDERING INFORMATION Select appropriate choice from each column

Mounting	No.	Finish	Lamp
PR Ground stake	6216 6219 6222 6223 7216 7223 9222	B Black Z Architectural Bronze DZ Dark Bronze LZ Light Bronze SB Special Bronze G Verde P Pewter BR Architectural Brick GT Granite TC Terracotta R Rust	LAMP See reference codes, pages 128-130 INTEGRATED LED See reference codes, page 130, group B

NOTE: not all accessories are available for all fixtures. See footnotes below before ordering. Fixtures shipped with standard lamp, unless otherwise specified, and with specified mounting hardware.

