



**MODEL PHT-6510** | Specification Sheet  
Residential Series • Specialty / Downlight

TYPE:  MODEL:

PROJECT:

**PRODUCT FEATURES**

Wattage	1 – 5 W
Voltage	9 – 15 VAC
Housing	Aluminum
Dimensions	6" W x 5 5/8" H (18 1/8" H with chains)



**ORDERING INFORMATION**

EXAMPLE: **PHT-6510-B-W-LB5ND**

CATEGORY	MODEL	FINISH	LED
PHT	6510		

CATEGORY	MODEL	FINISH	LED
PHT Hanging Downlight	6510	<b>B</b> Black	<b>W-LB2ND</b> 2.5 Watts   Warm   Integrated LED
		<b>Z</b> Architectural Bronze	<b>N-LB2ND</b> 2.5 Watts   Neutral   Integrated LED
		<b>DZ</b> Dark Bronze	<b>C-LB2ND</b> 2.5 Watts   Cool   Integrated LED
		<b>GT</b> Granite	<b>W-LB5ND</b> 5 Watts   Warm   Integrated LED
		<b>W</b> White	<b>N-LB5ND</b> 5 Watts   Neutral   Integrated LED
		<b>BR</b> Architectural Brick	<b>C-LB5ND</b> 5 Watts   Cool   Integrated LED
		<b>LZ</b> Light Bronze	<b>150-W-G4</b> 1.5 Watts   Warm   G4 LED Lamp
		<b>SB</b> Special Bronze	<b>NL</b> No Lamp
		<b>GG</b> Glossy Gray	
		<b>R</b> Rust	
		<b>HG</b> Hunter Green	
		<b>WB</b> Weathered Bronze	
		<b>WI</b> Weathered Iron	
		<b>GM</b> Graphite Metallic	
		<b>G</b> Verde	
<b>P</b> Pewter			
<b>M</b> Mocha			
<b>OF</b> Olde Finish			



**PROFESSIONAL  
OUTDOOR LIGHTING**

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)  
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



**SPECIFICATIONS**

**HOUSING CONSTRUCTION:**

Die-cast A360 aluminum with stamped aluminum petals and 12" plant-hanging chains to support planting containers.

**FINISH:**

Powder coat finish available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

**LENS:**

Clear, high-impact polycarbonate lens.

**MOUNTING:**

Solid brass loop with a six-foot stainless steel cable-hanger included.

**FASTENERS:**

All fasteners are stainless steel.

**WIRING:**

Prewired with a 36" pigtail of 18-2 SPT1 UV resistant cable and watertight connectors.

**CERTIFICATION:**

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

**LED:**

- Integrated LED Module. 2.5 – 5 Watts.
- G4 LED Lamp. 1.5 Watts.

**ELECTRICAL:**

Input voltage range 9 - 15 VAC.  
Low voltage transformer required to operate (sold separately).

**DIMENSIONS**

