




5260 Aluminum | 50 W max (halogen) | MR-16 Lamp or LED | LN-20 BAB/FG Std




5261 Aluminum | 50 W max (halogen) | MR-16 Lamp or LED | LN-20 BAB/FG Std



5262 Aluminum | 50 W max (halogen) | MR-16 Lamp or LED | LN-20 BAB/FG Std



5263 Aluminum | 50 W max (halogen) | MR-16 Lamp or LED | LN-20 BAB/FG Std



HOUSING/LENS COVER

- » Die-cast copper-free aluminum
- » Silicone O-ring gasket
- » Superior weather-tight seal

FINISH

- » Polyester powder-coated finish. See ordering information for available colors.

SOCKET/LAMP HOLDER

- » Proprietary ceramic socket
- » Stainless steel springs
- » Nickel contacts
- » Teflon-jacketed wire leads

OPTICS/AIMING

- » Adjustable and lockable lamp bracket
- » ±25° of tilt
- » 360° rotation of housing

PHOTOMETRICS

- » For photometric data, see pages 131-149.

MOUNTING

- » In-grade
- » Conduit mount option has two 3/4" NPT inlets
- » Optional concrete mounting kit available, see page 127.

FASTENERS

- » Stainless steel fasteners

WIRING

- » Prewired with a three-foot pigtail of 18-2 direct-burial cable and underground connectors for a secure connection to the supply cable.

LENS

Model	Options	Properties
5260	» Convex	» Shock- and heat-resistant » Soda-lime glass » For optical effect lenses, see ordering information.
	» Clear	
	» Tempered	
5261	» Convex	» Shock- and heat-resistant » Soda-lime glass » For optical effect lenses, see ordering information.
	» Clear	
	» Tempered	
5262	» Convex	» Shock- and heat-resistant » Soda-lime glass » For optical effect lenses, see ordering information.
	» Clear	
	» Tempered	
5263	» Dual lens	» Shock- and heat-resistant » Soda-lime glass » For optical effect lenses, see ordering information.
	» Frosted flat outer lens	
	» Clear convex inner lens	
	» Tempered	

LED SPECIFICATIONS Look for this mark on products where LED options are available.

LED Lamp	Integrated LED
High Output Plug-in LED lamp with Vista exclusive smart-driver, powered to operate for 30,000 hours with an operating voltage of 9-15 VAC. See page 128 for extended specifications and options.	High Output LED lamp assembly with Vista exclusive smart-driver, powered to operate for 50,000 hours with an operating voltage of 9-15 VAC. See page 130 for extended specifications and options.

ORDERING INFORMATION Select appropriate choice from each column **example: GW-5271-B-BAB/FG-CBL**

Mounting	No.	Finish	Lamp	Lenses/Accessories
GW In-grade	5260	B Black	LAMP	CBL Convex Cool-Blue Lens
CM In-grade conduit mount	5261	Z Architectural Bronze	See reference codes, pages 128-130	CFR Convex Frosted Lens
	5262	DZ Dark Bronze		SL Flat Spread Lens
	5263 *	LZ Light Bronze		DBL Flat Dark Blue Lens
		SB Special Bronze	INTEGRATED LED	GL Flat Dark Green Lens
		G Verde	See reference codes, page 130, group F	RL Flat Red Lens
		P Pewter		YL Flat Amber Lens
		BR Architectural Brick		HL Honeycomb Louver
		GT Granite		JBCP-150 Concrete Mounting Kit
		TC Terracotta		
		R Rust		
		HG Hunter Green		
		M Mocha		
		WB Weathered Bronze		
		WI Weathered Iron		
		W White		

NOTE: not all accessories are available for all fixtures. See footnotes below before ordering.
 * No Lenses/Accessories available except for JBCP-150.
 Fixtures shipped with standard lamp, unless otherwise specified, and with specified mounting hardware.