



MODEL 5105 – BSO | Specification Sheet
Residential Series • Up / Accent / Downlight

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES



Wattage	2 – 4 W
Voltage	9 – 15 VAC
CCT	3000K, 4000K, 5000K
Housing	Die-cast Brass
Dimensions	3¼" W x 3" H x 2" D



ORDERING INFORMATION

EXAMPLE: GR-5105-BSO-2-W-FR

MOUNTING	MODEL	FINISH	WATTAGE	COLOR TEMP	ACCESSORIES
	5105	BSO			

MOUNTING	MODEL	FINISH	WATTAGE	COLOR TEMP	ACCESSORIES
GR ABS Ground Stake WR Wall-Mount Canopy TR Tree-Mount Junction Box	5105	BSO Olde Brass	2 2 Watts 3 3 Watts 4 4 Watts	W 3000K N 4000K C 5000K	FR Frosted Lens 5 5' Wire Lead ORDERING NOTES Fixtures shipped with specified mounting hardware. If fixture is to be used in conjunction with Extended Arm Mount (EAM): Must specify with extended wire length



PROFESSIONAL
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

HOUSING CONSTRUCTION:

Die-cast Brass.

FINISH:

Olde Brass.

LENS:

Clear, tempered glass lens.
Optical effect lenses are available.

FASTENERS:

All fasteners are stainless steel.

WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

MOUNTING:

Injection-molded composite knuckle with 1/2" NPS thread.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

LED:

Performance LED.
2 – 4 Watts.

COLOR TEMPERATURE:

3000K, 4000K or 5000K CCT White.

ELECTRICAL:

Input voltage range 9 - 15 VAC.
Low voltage transformer required to operate (sold separately).

DIMENSIONS

