



MODEL 2151 | Specification Sheet
Residential Series • Brass & Copper • Downlight

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES



Wattage	4.5 W or 5.5 W
Voltage	9 – 15 VAC
Lumens	295 or 389 Lumens
Lamp Type	MR-16 LED
Housing	Copper
Dimensions	2 1/8" DIA x 5 3/4" D x 3 1/4" W



ORDERING INFORMATION

EXAMPLE: DL-2151-CSN-4.5-W-36-FR

CATEGORY	MODEL	FINISH	LED	ACCESSORIES
DL	2151	CSN		

CATEGORY	MODEL	FINISH	LED	ACCESSORIES
DL Wall-Mount	2151	CSN Natural Copper	4.5-W-15 4.5 Watts Warm 15° Narrow Spot	FR Frosted Lens
			4.5-W-25 4.5 Watts Warm 25° Spot	BL Flat Cool Blue Lens
			4.5-W-36 4.5 Watts Warm 36° Flood	SL Flat Spread Lens
			4.5-W-60 4.5 Watts Warm 60° Wide Flood	DBL Flat Dark Blue Lens
			5.5-W-15 5.5 Watts Warm 15° Narrow Spot	GL Flat Dark Green Lens
			5.5-W-25 5.5 Watts Warm 25° Spot	RL Flat Red Lens
			5.5-W-36 5.5 Watts Warm 36° Flood	YL Flat Amber Lens
			5.5-W-60 5.5 Watts Warm 60° Wide Flood	HL Honeycomb louver
			NL No Lamp	



PROFESSIONAL
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

HOUSING CONSTRUCTION:

Heavy-gauge, extruded copper with machined solid brass base.

FINISH:

Brushed Natural Copper.
(Brushed copper will rapidly age to an elegant rich bronze-like color and may develop areas of patina over time.)

LENS:

Clear, tempered glass lens.
Optical effect lenses are available.

MOUNTING:

Adjustable bracket and J-Box included.

FASTENERS:

Fasteners are stainless steel or brass.

WIRING:

Prewired with a 36" pigtail of 18-2 SPT1 UV resistant cable and watertight connectors.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

LED:

MR-16 LED Lamp.
295 or 389 Lumens.
4.5 or 5.5 Watts.

LIGHT DISTRIBUTION:

Very Narrow Spot **15** (15°)
Narrow Spot **25** (25°)
Medium Flood **36** (36°)
Wide Flood **60** (60°)

ELECTRICAL:

Input voltage range 9 - 15 VAC.
Low voltage transformer required to operate (sold separately).

DIMENSIONS

