



2521 Aluminum | 35 W max (halogen) | MR-16 Lamp or LED | LN-20 BAB Std




2522 Aluminum | 35 W max (halogen) | MR-16 Lamp or LED | LN-20 BAB Std




<b>HOUSING</b>
Available options: » Copper-free aluminum » Solid Brass » Solid Copper » Stainless steel
<b>FINISH</b>
» For available options, see ordering information.
<b>SOCKET/LAMP HOLDER</b>
» Top grade Noryl polymer socket » Phosphor bronze contacts » PVC-jacketed wire leads » Stainless steel lamp holder
<b>LENS</b>
» Clear » Tempered » Shock- and heat-resistant » Soda-lime glass » For optical effect lenses, see ordering information.

<b>LAMP TYPE</b>
» Standard lamp included with fixture. For other lamp and wattage options see Lamp Guide, pages 128-130.
<b>PHOTOMETRICS</b>
» For photometric data, see pages 131-149.
<b>MOUNTING</b>
» Wall mount canopy
<b>FASTENERS</b>
» Stainless steel fasteners
<b>WIRING</b>
» Prewired with a three-foot pigtail of 18-2 direct-burial cable and underground connectors for a secure connection to the supply cable.

2221 Aluminum | 20 W max (halogen) | T5 Wedge Lamp | LN-912 T5 Std



2222 Aluminum | 20 W max (halogen) | T5 Wedge Lamp | LN-912 T5 Std



<b>2221 / 2222</b>
<b>HOUSING</b>
» Extruded » Copper-free aluminum
<b>FINISH</b>
» Polyester powder-coated finish. See ordering information for available colors.
<b>SOCKET/LAMP HOLDER</b>
» Top grade polymer socket » Phosphor bronze contacts » PVC-jacketed wire leads
<b>LAMP TYPE</b>
» Standard lamp included with fixture. For other lamp and wattage options see Lamp Guide, pages 128-130.
<b>PHOTOMETRICS</b>
» For photometric data, see pages 131-149.
<b>MOUNTING</b>
» Wall mount canopy
<b>FASTENERS</b>
» Stainless steel and brass fasteners
<b>WIRING</b>
» Prewired with a three-foot pigtail of 18-2 SPT1 UV-resistant cable and weather resistant connectors for a secure connection to the supply cable.

**LED SPECIFICATIONS** Look for this mark on products where LED options are available.

**LED Lamp**  
High Output Plug-in LED lamp with Vista exclusive smart-driver, powered to operate for 30,000 hours with an operating voltage of 9-15 VAC. See page 128 for extended specifications and options.

**ORDERING INFORMATION** Select appropriate choice from each column **example: WR-2522-B-20 BAB-CBL**

Mounting	No.	Finish	Lamp	Lenses/Accessories
WR Wall mount canopy	2221 * 2222 * 2521 2522	B Black Z Architectural Bronze DZ Dark Bronze LZ Light Bronze SB Special Bronze G Verde P Pewter BR Architectural Brick GT Granite TC Terracotta R Rust HG Hunter Green M Mocha WB Weathered Bronze WI Weathered Iron W White  BSN Natural Brass ** BSO Natural Brass w/Olde Brass finish ** CSN Natural Copper ** SS Natural Stainless Steel **	See reference codes, pages 128-130	CBL Convex Cool Blue Lens CFR Convex Frosted Lens SL Flat Spread Lens DBL Flat Dark Blue Lens GL Flat Dark Green Lens RL Flat Red Lens YL Flat Amber Lens HL Honeycomb Louver

**NOTE: not all accessories are available for all fixtures. See footnotes below before ordering.**  
\* Accessory lenses not available.  
\*\* Only available for models 2521 and 2522.  
Fixtures shipped with standard lamp, unless otherwise specified, and with specified mounting hardware.