



**MODEL 9226** | Specification Sheet  
Residential Series • Bollard

TYPE:  MODEL:

PROJECT:

**PRODUCT FEATURES**

Wattage	1.5 W
Voltage	9 – 15 VAC
Lamp Type	G4 LED
Housing	Aluminum
Dimensions	10" DIA x 31 1/4" H (above grade)   43 1/4" H (over all)



**ORDERING INFORMATION**

EXAMPLE: PR-9226-B-150-W-G4-RS

MOUNTING	MODEL	FINISH	LED	ACCESSORIES
BR	9226			

MOUNTING	MODEL	FINISH	LED	ACCESSORIES
<b>BR</b> Direct-burial Post	<b>9226</b>	<b>B</b> Black	<b>150-W-G4</b> 1.5 Watts   Warm   G4 LED Lamp <b>NL</b> No Lamp	<b>RS</b> 180° Reflector Shield
		<b>Z</b> Architectural Bronze		
		<b>DZ</b> Dark Bronze		
		<b>GT</b> Granite		
		<b>W</b> White		
		<b>BR</b> Architectural Brick		
		<b>LZ</b> Light Bronze		
		<b>SB</b> Special Bronze		
		<b>GG</b> Glossy Gray		
		<b>R</b> Rust		
		<b>HG</b> Hunter Green		
		<b>WB</b> Weathered Bronze		
		<b>WI</b> Weathered Iron		
		<b>GM</b> Graphite Metallic		
		<b>G</b> Verde		
<b>P</b> Pewter				
<b>M</b> Mocha				
<b>OF</b> Olde Finish				



PROFESSIONAL  
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)  
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



**SPECIFICATIONS**

**HOUSING CONSTRUCTION:**

Die-cast A360 aluminum.

**POST CONSTRUCTION:**

Extruded Aluminum (1/8" wall thickness).

**FINISH:**

Powder coat finish available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

**LENS:**

Clear, prismatic, high-impact polycarbonate lens.

**MOUNTING:**

Direct-burial Post. (Post extended 12" for in-ground or concrete mounting.)

**FASTENERS:**

All fasteners are stainless steel.

**WIRING:**

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

**CERTIFICATION:**

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

**LED:**

G4 LED Lamp.  
1.5 Watts.

**ELECTRICAL:**

Input voltage range 9 - 15 VAC.  
Low voltage transformer required to operate (sold separately).

**DIMENSIONS**

