



MODEL 5014i | Specification Sheet
Residential Series • Up / Accent / Downlight

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES



| | |
|--------------|------------------------------|
| Wattage | 1.5 – 3.5 W |
| Voltage | 9 – 15 VAC |
| Lumens | 180 – 400 Delivered Lumens |
| Distribution | 25° (SP), 36° (MF), 60° (WF) |
| CCT | 3000K, 4000K, 5000K |
| CRI | 80 CRI min. |
| Housing | Die-cast Aluminum |
| Dimensions | 2 1/8" DIA x 5 1/4" D |



ORDERING INFORMATION

EXAMPLE: GR-5014i-B-2.5-W-SP-HL

| MOUNTING | MODEL | FINISH | WATTAGE | COLOR TEMP | DISTRIBUTION | ACCESSORIES |
|----------|-------|--------|---------|------------|--------------|-------------|
| | 5014i | | | | | |

| MOUNTING | MODEL | FINISH |
|--|--------------|---|
| GR ABS ground stake WR Wall-mount canopy TR Tree-mount junction box | 5014i | B Black Z Architectural Bronze DZ Dark Bronze GT Granite W White BR Architectural Brick LZ Light Bronze SB Special Bronze GG Glossy Gray R Rust HG Hunter Green WB Weathered Bronze WI Weathered Iron GM Graphite Metallic G Verde P Pewter M Mocha OF Olde Finish |

| WATTAGE | COLOR TEMPERATURE | DISTRIBUTION | ACCESSORIES | ORDERING NOTES |
|--|--|---|---|---|
| 1.5 1.5 Watts 2.5 2.5 Watts 3.5 3.5 Watts | W 3000K N 4000K C 5000K | SP 25° Spot MF 36° Flood WF 60° Wide Flood | FR Frosted Lens 5 5' Wire Lead | Fixtures shipped with specified mounting hardware. If fixture is to be used in conjunction with Extended Arm Mount (EAM): Must specify with extended wire length Wireless Control RGBW Smart LED available. Consult Vista Customer Service for details. |



PROFESSIONAL
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

HOUSING CONSTRUCTION:

Die-cast A360 aluminum.

FINISH:

Powder coat finish available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish. Custom Powder coat finishes available on request.

LENS:

Clear, tempered glass lens.
Optical effect lenses are available.

FASTENERS:

All fasteners are stainless steel.

WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

MOUNTING:

Injection-molded composite knuckle with 1/2" NPS thread.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

LED:

Performance LED.
180 – 400 Lumens delivered.
1.5 – 3.5 Watts.

COLOR TEMPERATURE:

3000K, 4000K or 5000K CCT White.

COLOR RENDERING:

80 CRI minimum

ELECTRICAL:

Input voltage range 9 - 15 VAC.
Low voltage transformer required to operate (sold separately).

LIGHT DISTRIBUTION:

Spot **SP** (25°)
Medium Flood **MF** (36°)
Wide Flood **WF** (60°)

DIMENSIONS

