





#### HOUSING

» Copper-free aluminum

## STEM

» ¼" Pipe

» Schedule 40 aluminum

#### FINISH

» Polyester powder-coated finish. See ordering information for available colors.

#### SOCKET/LAMP HOLDER

- » Proprietary ceramic socket
- » Stainless steel springs
- » Nickel contacts
  - » Teflon-jacketed wire leads

#### LENS

» Clear

» High impact polycarbonate

#### LAMP TYPE

» Standard lamp included with fixture. For other lamp and wattage options see Lamp Guide, pages 128-130.

### PHOTOMETRICS

» For photometric data, see pages 131-149.

#### MOUNTING

- »  $\frac{1}{2}$ " NPT custom bushing on bottom of stem
- » Stress dispersing collar
- » Fixture may be mounted into threaded hubs in junction boxes, ground stakes, or mounting canopies.
- See ordering information for mounting options. For optional mounting accessories, see pages 126-127.

#### **FASTENERS**

» Stainless steel fasteners

#### WIRING


» Prewired with a three-foot pigtail of 18-2 direct-burial cable and underground connectors for a secure connection to the supply cable.




# 7210 20 W max (halogen) T3 Lamp or LED LN-10 T3 Std









LED Lamp

to operate for 30,000 hours with an operating voltage of 9-15 VAC. See page 128 for extended specifications and options.

Integrated LED

High Output Plug-in LED lamp with Vista exclusive smart-driver, powered to operate for 30,000 hours with an operating voltage of 9-15 VAC.

High Output LED lamp assembly with Vista exclusive smart-driver, powered to operate for 50,000 hours with an operating voltage of 9-15 VAC. See page 130 for extended specifications and options.

ORDERING INFORMATION			e	example: PR-6506-B-10
Mounting	No.	Finish	Lamp	Lenses/Accessories
PR Ground stake	6506 6508 7210 9265	B Black Z Architectural Bronze DZ Dark Bronze LZ Light Bronze SB Special Bronze G Verde P Pewter BR Architectural Brick GT Granite TC Terracotta R Rust HG Hunter Green M Mocha WB Weathered Bronze WI Weathered Iron W White	LAMP See reference codes, pages 128-130 INTEGRATED LED See reference codes, page 130, group B	FR Flat Frosted Lens

