



TYPE:  MODEL:

PROJECT:

**PRODUCT DESCRIPTION**



|                                   |        |
|-----------------------------------|--------|
| 5006 Uplight                      | Qty 6  |
| 6500 Pathlight                    | Qty 4  |
| ES-150 Transformer                | Qty 1  |
| TC-112 Timer                      | Qty 1  |
| GS-150 ABS Ground Stake           | Qty 10 |
| Gel-Filled Underground Connectors | Qty 20 |



**5006 FEATURES**



|            |  |
|------------|--|
| LED Type   | 4.5W   36° LED MR-16   |
| Voltage    | 9 – 15 VAC   |
| Lumens     | 295 Lumens   |
| Housing    | Die-cast A360 Aluminum   |
| Finish     | Powder coat finish available in Black, Architectural Bronze or Dark Bronze |
| Lens       | Clear Tempered Glass   |
| Mounting   | Injection-molded composite knuckle with 1/2" NPS thread                    |
| Dimensions | 2" DIA x 5 3/4" D  |





**6500 FEATURES**



|            |  |
|------------|--|
| LED Type   | 1.5W LED G4 Bi-Pin   |
| Voltage    | 9 – 15 VAC   |
| Housing    | Die-cast A360 Aluminum   |
| Finish     | Powder coat finish available in Black, Architectural Bronze or Dark Bronze |
| Lens       | Clear Polycarbonate  |
| Mounting   | Bottom of stem threaded with 1/2" NPT                                      |
| Dimensions | 6" DIA x 19 1/2" H   |



**ES-150 FEATURES**



|                       |                                 |
|-----------------------|---------------------------------|
| Wattage               | 150 W                           |
| Primary Voltage       | 120 VAC                         |
| Secondary Voltage     | 12 and 15 VAC                   |
| Housing               | 20-gauge 304 stainless steel    |
| Finish                | Clear powder coat finish        |
| Nema Enclosure Rating | 3R                              |
| Dimensions            | 11 3/4" H x 6 1/8" W x 5 1/4" D |





**TC-112 FEATURES**



|                         |                        |
|-------------------------|------------------------|
| Input Voltage           | 120 VAC                |
| Current Rating          | 9 A                    |
| Wattage                 | 1125 W                 |
| Program ON/OFF settings | 2                      |
| Minimum ON/OFF Times    | 30 min.                |
| Mechanism Type          | Analog/Mechanical      |
| Dimensions              | 3 1/8" H x 3" W x 2" D |



**GS-150 FEATURES**



|                  |                   |
|------------------|-------------------|
| Type             | Ground Stake      |
| Material         | ABS               |
| Fixture Mounting | 1/2" FPT Base     |
| Dimensions       | 9" H x 2 3/8" DIA |

