



TYPE: MODEL:
PROJECT:

PRODUCT DESCRIPTION



2216 Uplight	Qty 6
4704 Pathlight	Qty 4
ES-150 Transformer	Qty 1
TC-112 Timer	Qty 1
GS-150 ABS Ground Stake	Qty 10
Gel-Filled Underground Connectors	Qty 20



2216 FEATURES



LED Type	4.5W 36° LED MR-16
Voltage	9 – 15 VAC
Lumens	295 Lumens
Housing	Die-cast A360 Aluminum
Finish	Powder coat finish available in Black, Architectural Bronze or Dark Bronze
Lens	Clear Tempered Glass
Mounting	Injection-molded composite knuckle with 1/2" NPS thread
Dimensions	2 1/2" DIA x 7 1/8" D





4704 FEATURES



LED Type	1.5W LED G4 Bi-Pin
Voltage	9 – 15 VAC
Housing	Die-cast A360 Aluminum
Finish	Powder coat finish available in Black, Architectural Bronze or Dark Bronze
Lens	Clear Polycarbonate
Mounting	Bottom of stem threaded with 1/2" NPT
Dimensions	7 3/8" DIA x 15 3/4" H



ES-150 FEATURES



Wattage	150 W
Primary Voltage	120 VAC
Secondary Voltage	12 and 15 VAC
Housing	20-gauge 304 stainless steel
Finish	Clear powder coat finish
Nema Enclosure Rating	3R
Dimensions	11 3/4" H x 6 1/8" W x 5 1/4" D





TC-112 FEATURES



Input Voltage	120 VAC
Current Rating	9 A
Wattage	1125 W
Program ON/OFF settings	2
Minimum ON/OFF Times	30 min.
Mechanism Type	Analog/Mechanical
Dimensions	3 1/8" H x 3" W x 2" D



GS-150 FEATURES



Type	Ground Stake
Material	ABS
Fixture Mounting	1/2" FPT Base
Dimensions	9" H x 2 3/8" DIA

