



**MODEL 4015** | Specification Sheet  
Residential Series • Specialty • Deck Light

TYPE:  MODEL:

PROJECT:

**PRODUCT FEATURES**

Wattage	4.5 W or 5.5 W
Voltage	9 – 15 VAC
Lumens	295 or 389 Lumens
Lamp Type	MR-16 LED
Housing	Aluminum
Dimensions	2 1/4" DIA x 4 1/4" D x 38" L



**ORDERING INFORMATION**

EXAMPLE: *FL-4015-B-4.5-W-36-FR*

CATEGORY	MODEL	FINISH	LED	ACCESSORIES
FL	4015	B		

CATEGORY	MODEL	FINISH	LED	ACCESSORIES
FL Flexible Stem Deck Light	4015	B Black	<b>4.5-W-15</b> 4.5 Watts   Warm   15° Narrow Spot	<b>FR</b> Frosted Lens
			<b>4.5-W-25</b> 4.5 Watts   Warm   25° Spot	<b>BL</b> Flat Cool Blue Lens
			<b>4.5-W-36</b> 4.5 Watts   Warm   36° Flood	<b>SL</b> Flat Spread Lens
			<b>4.5-W-60</b> 4.5 Watts   Warm   60° Wide Flood	<b>DBL</b> Flat Dark Blue Lens
			<b>5.5-W-15</b> 5.5 Watts   Warm   15° Narrow Spot	<b>GL</b> Flat Dark Green Lens
			<b>5.5-W-25</b> 5.5 Watts   Warm   25° Spot	<b>RL</b> Flat Red Lens
			<b>5.5-W-36</b> 5.5 Watts   Warm   36° Flood	<b>YL</b> Flat Amber Lens
			<b>5.5-W-60</b> 5.5 Watts   Warm   60° Wide Flood	<b>HL</b> Honeycomb louver
			<b>NL</b> No Lamp	



**PROFESSIONAL  
OUTDOOR LIGHTING**

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)  
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



**SPECIFICATIONS**

**HOUSING CONSTRUCTION:**

Heavy gauge extruded aluminum.

**STEM CONSTRUCTION:**

Heavy gauge, adjustable, nickel plated stainless steel tubing.  
Incased in black UV resistant PVC.

**FINISH:**

Housing & Base powder coat finished in Black.

**LENS:**

Clear, tempered glass lens.  
Optical effect lenses are available.

**MOUNTING:**

Bottom of stem threaded into CNC-machined solid aluminum mounting canopy.

**FASTENERS/INSERTS:**

All fasteners are stainless steel.

**WIRING:**

Prewired with a 36" pigtail of 18-2 SPT1 UV resistant cable and watertight connectors.

**CERTIFICATION:**

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

**LED:**

MR-16 LED Lamp.  
295 or 389 Lumens.  
4.5 or 5.5 Watts.

**ELECTRICAL:**

Input voltage range 9 - 15 VAC.  
Low voltage transformer required to operate (sold separately).

**LIGHT DISTRIBUTION:**

Very Narrow Spot **15** (15°)  
Narrow Spot **25** (25°)  
Medium Flood **36** (36°)  
Wide Flood **60** (60°)

**DIMENSIONS**

