



MODEL 2145 | Specification Sheet
Residential Series • Brass & Copper • Step Light

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES



Wattage 1 – 5 W

Voltage 9 – 15 VAC

Faceplate Brass, Copper or Stainless Steel

Dimensions 9 1/8" L x 2 7/8" H x 3 1/2" D

ORDERING INFORMATION

EXAMPLE: SL-2145-BSN-W-LC5ND

CATEGORY SL **MODEL** 2145 **FINISH** **LED**

CATEGORY	MODEL	FINISH	LED
SL Step Light	2145	BSN Natural Brass	W-LC5ND 5 Watts Warm Integrated LED
		BSO Olde Brass	N-LC5ND 5 Watts Neutral Integrated LED
		CSN Natural Copper	C-LC5ND 5 Watts Cool Integrated LED
		SS Stainless Steel	2.5-W-G-T3 2.5 Watts Warm T3 LED Lamp
			150-W-G4 1.5 Watts Warm G4 LED Lamp (x 2)
			NL No Lamp





SPECIFICATIONS

HOUSING CONSTRUCTION:

Stamped & formed aluminum recessed box with 1/2" knockouts on the back & side.

COVER PLATE CONSTRUCTION:

Stamped solid brass, copper, or stainless steel.

LENS:

Translucent, high-impact polycarbonate lens.

MOUNTING:

Recessed mounting box included.

FASTENERS:

All fasteners are stainless steel.

WIRING:

Prewired with a 36" pigtail of 18-2 direct-burial cable and underground connectors.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

LED:

- Integrated LED Module. 5 Watts.
- G4 LED Lamp (x 2). 1.5 Watts (x 2).

ELECTRICAL:

Input voltage range 9 - 15 VAC.
Low voltage transformer required to operate (sold separately).

DIMENSIONS

