



MODEL 2150 | Specification Sheet
Residential Series • Brass & Copper • Downlight

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES



Wattage	4.5 W or 5.5 W
Voltage	9 – 15 VAC
Lumens	295 or 389 Lumens
Lamp Type	MR-16 LED
Housing	Copper or Stainless Steel
Dimensions	2 1/8" DIA x 4 1/2" H

ORDERING INFORMATION

EXAMPLE: HT-2150-CSN-4.5-W-36

CATEGORY	MODEL	FINISH	LED	ACCESSORIES
HT	2150			

CATEGORY	MODEL	FINISH	LED	ACCESSORIES
HT Hanging Downlight	2150	CSN Natural Copper	4.5-W-15 4.5 Watts Warm 15° Narrow Spot	BL Flat Cool Blue Lens
			4.5-W-25 4.5 Watts Warm 25° Spot	SL Flat Spread Lens
		SS Stainless Steel	4.5-W-36 4.5 Watts Warm 36° Flood	DBL Flat Dark Blue Lens
			4.5-W-60 4.5 Watts Warm 60° Wide Flood	GL Flat Dark Green Lens
		NL No Lamp	5.5-W-15 5.5 Watts Warm 15° Narrow Spot	RL Flat Red Lens
			5.5-W-25 5.5 Watts Warm 25° Spot	YL Flat Amber Lens
			5.5-W-36 5.5 Watts Warm 36° Flood	HL Honeycomb louver
			5.5-W-60 5.5 Watts Warm 60° Wide Flood	



PROFESSIONAL
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

CONSTRUCTION:

Heavy-gauge, extruded, copper or stainless steel fitted with machined solid brass base.

FINISH:

Brushed Natural Copper or Stainless Steel.
(Brushed copper will rapidly age to an elegant rich bronze-like color and may develop areas of patina over time.)

LENS:

Clear, tempered glass lens.
Optical effect lenses are available

MOUNTING:

Solid brass loop with a six-foot stainless steel cable-hanger included.

FASTENERS:

All fasteners are stainless steel.

WIRING:

Prewired with a 36" pigtail of 18-2 SPT1 UV resistant cable and watertight connectors.

CERTIFICATION:

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

LED:

MR-16 LED Lamp.
295 or 389 Lumens.
4.5 or 5.5 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC.
Low voltage transformer required to operate (sold separately).

DIMENSIONS

