



**MODEL 4261M** | Specification Sheet  
Residential Series • Step Light

TYPE:  MODEL:

PROJECT:

**PRODUCT FEATURES**



Wattage 2 W

Voltage 9 – 15 VAC

Shroud Brass, Copper or Stainless Steel

Dimensions 12 ¼" L x 1 ¼" H x 6" D

**ORDERING INFORMATION**

EXAMPLE: *SL-4261M-B-W-LB2ND*

CATEGORY	MODEL	FINISH	LED
SL	4261M		

CATEGORY	MODEL	FINISH	LED
SL Step Light	4261M	<b>B</b> Black <b>R</b> Rust <b>Z</b> Architectural Bronze <b>HG</b> Hunter Green <b>DZ</b> Dark Bronze <b>WB</b> Weathered Bronze <b>GT</b> Granite <b>WI</b> Weathered Iron <b>W</b> White <b>GM</b> Graphite Metallic <b>BR</b> Architectural Brick <b>G</b> Verde <b>LZ</b> Light Bronze <b>P</b> Pewter <b>SB</b> Special Bronze <b>M</b> Mocha <b>GG</b> Glossy Gray <b>OF</b> Olde Finish	<b>W-LB2ND</b> 2 Watts total   Warm   Integrated LED <b>C-LB2ND</b> 2 Watts total   Cool   Integrated LED
		<b>BSN</b> Natural Brass <b>CSN</b> Natural Copper <b>BSO</b> Olde Brass <b>SS</b> Stainless Steel	



**PROFESSIONAL  
OUTDOOR LIGHTING**

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)  
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



**SPECIFICATIONS**

**SHROUD CONSTRUCTION:**  
Brass, Copper or Stainless Steel.

**HOUSING CONSTRUCTION:**  
Die-cast A360 aluminum.

**FINISH:**  
Available with Powder coat finish in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

**LENS:**  
Textured, high-impact polycarbonate lens.

**FASTENERS:**  
All fasteners are stainless steel.

**WIRING:**  
Prewired with a ten-foot pigtail of 18-2 SPT1 cable and underground connectors.

**CERTIFICATION:**  
UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

**LED:**  
Integrated LED Module.  
2 Watts total.

**ELECTRICAL:**  
Input voltage range 9 - 15 VAC.  
Low voltage transformer required to operate (sold separately).

**DIMENSIONS**

